

SDI Limited

Version No: 6.1.1.1 Safety Data Sheet (Conforms to Regulations (EC) No 2015/830) Issue Date: **18/03/2016** Print Date: **24/03/2016** Initial Date: **Not Available** L.REACH.GBR.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1.Product Identifier

Product name	Pola Office Powder
Synonyms	Not Available
Other means of identification	Not Available

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	To remove discoloration of teeth, to be performed by a dentist.	
Uses advised against	Not Applicable	

1.3. Details of the supplier of the safety data sheet

Registered company name	SDI Limited	SDI Brazil Industria E Comercio Ltda	SDI Germany GmbH		
Address	3-15 Brunsdon Street VIC Bayswater 3153 Australia	Rua Dr. Virgilio de Carvalho Pinto, 612 São Paulo CEP 05415-020 Brazil	Hansestrasse 85 Cologne D-51149 Germany		
Telephone	+61 3 8727 7111 (Business Hours) +55 11 3092 7100 +49 0 2203 9255 0				
Fax	+61 3 8727 7222 +55 11 3092 7101 +49 0 2203 9255 200				
Website	www.sdi.com.au www.sdi.com.au				
Email	info@sdi.com.au	brasil@sdi.com.au	germany@sdi.com.au		
Registered company name	SDI (North America) Inc.				
Address	1279 Hamilton Parkway IL Itasca 60143 United States				
Telephone	+1 630 361 9200 (Business hours)				
Fax	Not Available				
Website	Not Available				
Email	USA.Canada@sdi.com.au				

1.4. Emergency telephone number

Association / Organisation	SDI Limited	Not Available	Not Available	
Association/ Organisation	SDi Limited Not Available Not Available			
Emergency telephone numbers	+61 3 8727 7111 Not Available Not Available			
Other emergency telephone numbers	ray.cahill@sdi.com.au Not Available Not Available			
Association / Organisation	Not Available			
Emergency telephone numbers	+61 3 8727 7111			
Other emergency telephone numbers	Not Available			

SECTION 2 HAZARDS IDENTIFICATION

2.1.Classification of the substance or mixture

Considered a dangerous mixture according to directive 1999/45/EC, Reg. (EC) No 1272/2008 (if applicable) and their amendments. Not classified as Dangerous Goods for transport purposes.

DSD classification	In case of mixtures, classification has been prepared by following DPD (Directive 1999/45/EC) and CLP Regulation (EC) No 1272/2008 regulations		
DPD classification ^[1]	R36/37/38 Irritating to eyes, respiratory system and skin.		
Legend:	1. Classification by vendor; 2. Classification drawn from EC Directive 67/548/EEC - Annex I; 3. Classification drawn from EC Directive 1272/2008 - Annex VI		

Classification according to regulation (EC) No 1272/2008 [CLP] ^[1]	Skin Corrosion/Irritation Category 2, Eye Irritation Category 2, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation)
Legend:	1. Classification by vendor; 2. Classification drawn from EC Directive 67/548/EEC - Annex I ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI
2.2. Label elements	
CLP label elements	
SIGNAL WORD	WARNING
Hazard statement(s)	
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

Supplementary statement(s)

Not Applicable

Precautionary statement(s) Prevention

P271	Use only outdoors or in a well-ventilated area.		
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.		
P280	P280 Wear protective gloves/protective clothing/eye protection/face protection.		

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.		
P337+P313	If eye irritation persists: Get medical advice/attention.		
P302+P352	IF ON SKIN: Wash with plenty of water and soap.		
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
P332+P313	If skin irritation occurs: Get medical advice/attention.		
P362+P364	Take off contaminated clothing and wash it before reuse.		

Precautionary statement(s) Storage

P405	Store locked up.	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	

Precautionary statement(s) Disposal

P501 Dis	Dispose of contents/container in accordance with local regulations.
-----------------	---

2.3. Other hazards

Cumulative effects may result following exposure*.

REACh - Art.57-59: The mixture does not contain Substances of Very High Concern (SVHC) at the SDS print date.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

3.1.Substances

See 'Composition on ingredients' in Section 3.2

3.2.Mixtures

1.CAS No 2.EC No 3.Index No 4.REACH No	%[weight]	Name	Classification according to directive 67/548/EEC [DSD]	Classification according to regulation (EC) No 1272/2008 [CLP]
1.Not Available 2.Not Available 3.Not Available 4.Not Available	70-75	silicone dioxide powder	Not Applicable	Not Applicable
Legend:	1. Classification by vendor; 2. Classification drawn from EC Directive 67/548/EEC - Annex I ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI 4. Classification drawn from C&L			

SECTION 4 FIRST AID MEASURES

General	 If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation. If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. If furnes or combustion products are inhaled remove from contaminated area. Seek medical attention. If swallowed do NOT induce vomiting. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.
Eye Contact	If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Seek medical attention.
Ingestion	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

5.1. Extinguishing media

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

5.2. Special hazards arising from the substrate or mixture

Fire Incompatibility	Reacts vigorously with alkali metals
5.3. Advice for firefighters	
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water courses. Use water delivered as a fine spray to control fire and cool adjacent area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use.
Fire/Explosion Hazard	 Combustible solid which burns but propagates flame with difficulty; it is estimated that most organic dusts are combustible (circa 70%) - according to the circumstances under which the combustion process occurs, such materials may cause fires and / or dust explosions. Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in air or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions). Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust (420 micron or less) may burn rapidly and fiercely if ignited - particles exceeding this limit will generally not form flammable dust clouds; once initiated, however, larger particles up to 1400 microns diameter will contribute to the propagation of an explosion. In the same way as gases and vapours, dusts in the form of a cloud are only ignitable over a range of concentrations; in principle, the concepts of lower explosive limit (LEL) and upper explosive limit (UEL) are applicable to dust clouds but only the LEL is of practical use; - this is because of the inherent difficulty of achieving homogeneous dust clouds at high temperatures (for dusts the LEL is often called the "Minimum Explosible Concentration", MEC). When processed with flammable liquids/vapors/mists, ignitable (hybrid) mixtures may be formed with combustible dust clouds - MIE) will be lower than the pure dust in air mixture. The Lower Explosive Limit (LEL) of the vapour/dust mixture will be lower than the individual LELs for the vapors/mists or dusts.

 A dust explosion may release of large quantities of gaseous products; this in turn creates a subsequent pressure rise of explosive force capable of damaging plant and buildings and injuring people. Usually the initial or primary explosion takes place in a confined space such as plant or machinery, and can be of sufficient force to damage or rupture the
plant. If the shock wave from the primary explosion enters the surrounding area, it will disturb any settled dust layers, forming a second dust cloud, and often initiate a much larger secondary explosion. All large scale explosions have resulted from chain reactions of this type.
 Dry dust can be charged electrostatically by turbulence, pneumatic transport, pouring, in exhaust ducts and during transport. Build-up of electrostatic charge may be prevented by bonding and grounding.
 Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting. All movable parts coming in contact with this material should have a speed of less than 1-meter/sec.
A sudden release of statically charged materials from storage or process equipment, particularly at elevated temperatures and/ or pressure, may result in ignition especially in the absence of an apparent ignition source.
One important effect of the particulate nature of powders is that the surface area and surface structure (and often moisture content) can vary widely from sample to sample, depending of how the powder was manufactured and handled; this means that it is virtually impossible to use flammability data published in the literature for dusts (in contrast to that published for gases and vapours).
Autoignition temperatures are often quoted for dust clouds (minimum ignition temperature (MIT)) and dust layers (layer ignition temperature (LIT)); LIT generally falls as the thickness of the layer increases.
Combustion products include; carbon monoxide (CO) carbon dioxide (CO2) silicon dioxide (SiO2) other pyrolysis products typical of burning organic material May emit poisonous fumes. May emit corrosive fumes.

SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures See section 8

6.2. Environmental precautions

See section 12

6.3. Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid breathing dust and contact with skin and eyes. Wear protective clothing, gloves, safety glasses and dust respirator. Use dry clean up procedures and avoid generating dust. Sweep up, shovel up or Vacuum up (consider explosion-proof machines designed to be grounded during storage and use). Place spilled material in clean, dry, sealable, labelled container.
Major Spills	Moderate hazard. CAUTION: Advise personnel in area. Alert Emergency Services and tell them location and nature of hazard. Control personal contact by wearing protective clothing. Prevent, by any means available, spillage from entering drains or water courses. Recover product wherever possible. IF DRY: Use dry clean up procedures and avoid generating dust. Collect residues and place in sealed plastic bags or other containers for disposal. IF WET: Vacuum/shovel up and place in labelled containers for disposal. ALWAYS: Wash area down with large amounts of water and prevent runoff into drains. If contamination of drains or waterways occurs, advise Emergency Services.

6.4. Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

7.1. Precautions for safe handling

Storage incompatibility

Avoid strong acids, bases.

Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. DO NOT allow material to contact humans, exposed food or food utensils. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
Fire and explosion protection	See section 5
Other information	Store between 2 and 8 deg C. Do not store in direct sunlight. Store in a dry and well ventilated-area, away from heat and sunlight.
Conditions for safe st	* orage, including any incompatibilities
Suitable container	DO NOT repack. Use containers supplied by manufacturer only.

7.3. Specific end use(s)

See section 1.2

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters

DERIVED NO EFFECT LEVEL (DNEL)

Not Available

PREDICTED NO EFFECT LEVEL (PNEC)

Not Available

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name		TWA	STEL	Peak		Notes
Not Available	Not Available	Not Available		Not Available	Not Available	Not Availab	ole	Not Available
EMERGENCY LIMITS								
Ingredient	Material name		TEEL-1		TEEL-2		TEEL-3	
Pola Office Powder	Not Available		Not Availa	able	Not Available		Not Availa	ble
Ingredient	Original IDLH				Revised IDLH			
silicone dioxide powder	Not Available				Not Available			

MATERIAL DATA

8.2. Exposure controls

	 Engineering controls are used to remove a hazard or place a barrier between the worker and the l effective in protecting workers and will typically be independent of worker interactions to provide this The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the rist Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if design the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. Local exhaust ventilation is required where solids are handled as powders or crystals; even with powdered by mutual friction. Exhaust ventilation should be designed to prevent accumulation and recirculation of particulate in spite of local exhaust an adverse concentration of the substance in air could occur, respirat consist of: (a): particle dust respirators, if necessary, combined with an absorption cartridge; (b): filter respirators with absorption cartridge or canister of the right type; (c): fresh-air hoods or masks Build-up of electrostatic charge on the dust particle, may be prevented by bonding and ground Powder handling equipment such as dust collectors, dryers and mills may require additional p Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, d required to efficiently remove the contaminant. 	s high level of protection. m the worker and ventilation that led properly. The design of a ven hen particulates are relatively land s in the workplace. itory protection should be conside ing. rotection measures such as exp	t strategically "adds" and titlation system must match rge, a certain proportion will dered. Such protection migh
8.2.1. Appropriate engineering controls	Type of Contaminant:		Air Speed:
	direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)	
	grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial rapid air motion).	velocity into zone of very high	2.5-10 m/s (500-2000 f/min.)
	Within each range the appropriate value depends on:		
	Lower end of the range	Upper end of the range	
	1: Room air currents minimal or favourable to capture	1: Disturbing room air curren	nts
	2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity	
	3: Intermittent, low production.	3: High production, heavy use	9
	4: Large hood or large air mass in motion	4: Small hood-local control o	nly
	Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple e of distance from the extraction point (in simple cases). Therefore the air speed at the extraction poind distance from the contaminating source. The air velocity at the extraction fan, for example, should b crusher dusts generated 2 metres distant from the extraction point. Other mechanical consideration apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more who	nt should be adjusted, according e a minimum of 4-10 m/s (800-2 ns, producing performance defic	gly, after reference to 000 f/min) for extraction of cits within the extraction
8.2.2. Personal protection			
Eve and face protection	 Safety glasses with side shields. Chemical goggles. 		

Eye and face protection

Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of

Hands/feet protection The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The set through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: • frequency and duration of contact, • chemical resistance of glove material, • glove thickness and • dexterity Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent). • When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.		 chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]
Hands/feet protection the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Hands/feet protection The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: infequency and duration of contact, chemical resistance of glove material, glove thickness and dexterity Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent). When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.1.0 r national equivalent) is recommended. When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.1.0 r national equivalent) is recommended. Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use. Contarninated gloves should be replaced. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. Body protection See Other protection below PVCc. apron.	Skin protection	See Hand protection below
Other protection Overalls. P.V.C. apron. Barrier cream. Skin cleansing cream. Eye wash unit. 	Hands/feet protection	 the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: frequency and duration of contact, chemical resistance of glove material, glove thickness and dexterity Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent). When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use. Contaminated gloves should be replaced.
Other protection P.V.C. apron. Barrier cream. Skin cleansing cream. Eye wash unit. Eye wash unit. 	Body protection	See Other protection below
Thermal hazards Not Available	Other protection	 P.V.C. apron. Barrier cream. Skin cleansing cream.
	Thermal hazards	Not Available

Respiratory protection

Particulate. (AS/NZS 1716 & 1715, EN 143:000 & 149:001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	P1 Air-line*	-	PAPR-P1 -
up to 50 x ES	Air-line**	P2	PAPR-P2
up to 100 x ES	-	P3	-
		Air-line*	-
100+ x ES	-	Air-line**	PAPR-P3

* - Negative pressure demand ** - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

8.2.3. Environmental exposure controls

See section 12

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

1

Appearance	Fluffy white speckled powder; insoluble in water.		
Physical state	Divided Solid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Applicable
Initial boiling point and boiling range (°C)	Not Applicable	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Applicable	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Applicable

Vapour pressure (kPa)	Not Applicable	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Available

9.2. Other information

Not Available

SECTION 10 STABILITY AND REACTIVITY

10.1.Reactivity	See section 7.2
10.2.Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
10.3. Possibility of hazardous reactions	See section 7.2
10.4. Conditions to avoid	See section 7.2
10.5. Incompatible materials	See section 7.2
10.6. Hazardous decomposition products	See section 5.3

SECTION 11 TOXICOLOGICAL INFORMATION

 \bigcirc

Mutagenicity

11.1. Information on toxicological effects

I. Information on toxic	Jogical effects	
Inhaled	Evidence shows, or practical experience predicts, that the material produces irritation of inhalation. In contrast to most organs, the lung is able to respond to a chemical insult I damage. The repair process, which initially evolved to protect mammalian lungs from for resulting in the impairment of gas exchange, the primary function of the lungs. Respirat the recruitment and activation of many cell types, mainly derived from the vascular syste Persons with impaired respiratory function, airway diseases and conditions such as en concentrations of particulate are inhaled. If prior damage to the circulatory or nervous systems has occurred or if kidney damage individuals who may be exposed to further risk if handling and use of the material result in excessive exposures. Effects on lungs are significantly enhanced in the presence of respirable particles. Over breathing difficulties leading to or symptomatic of impaired respiratory function.	by first removing or neutralising the irritant and then repairing the oreign matter and antigens, may however, produce further lung damage atory tract irritation often results in an inflammatory response involving m. nphysema or chronic bronchitis, may incur further disability if excessive thas been sustained, proper screenings should be conducted on
Ingestion	The material has NOT been classified by EC Directives or other classification systems animal or human evidence. The material may still be damaging to the health of the indi kidney) damage is evident. Present definitions of harmful or toxic substances are gener morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea ar quantities is not thought to be cause for concern. Not normally a hazard due to the physical form of product. The material is a physical ir	ividual, following ingestion, especially where pre-existing organ (e.g liver, rally based on doses producing mortality rather than those producing nd vomiting. In an occupational setting however, ingestion of insignificant
Skin Contact	Evidence exists, or practical experience predicts, that the material either produces infla direct contact, and/or produces significant inflammation when applied to the healthy inta twenty-four hours or more after the end of the exposure period. Skin irritation may also I form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin rer blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic lev (spongiosis) and intracellular oedema of the epidermis. The material may accentuate any pre-existing dermatitis condition Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or I skin prior to the use of the material and ensure that any external damage is suitably prof	act skin of animals, for up to four hours, such inflammation being present be present after prolonged or repeated exposure; this may result in a adness (erythema) and swelling (oedema) which may progress to rel there may be intercellular oedema of the spongy layer of the skin lesions, may produce systemic injury with harmful effects. Examine the
Eye	Evidence exists, or practical experience predicts, that the material may cause eye irritat ocular lesions which are present twenty-four hours or more after instillation into the eye Repeated or prolonged eye contact may cause inflammation characterised by tempora temporary impairment of vision and/or other transient eye damage/ulceration may occur	tion in a substantial number of individuals and/or may produce significant a(s) of experimental animals.
		r.
Chronic	Long-term exposure to respiratory irritants may result in disease of the airways involvir Limited evidence suggests that repeated or long-term occupational exposure may prod	ng difficult breathing and related systemic problems.
Chronic	Limited evidence suggests that repeated or long-term occupational exposure may prod	ng difficult breathing and related systemic problems. Juce cumulative health effects involving organs or biochemical systems.
Chronic Pola Office Powder	Limited evidence suggests that repeated or long-term occupational exposure may prod TOXICITY IRR	ng difficult breathing and related systemic problems.
	Limited evidence suggests that repeated or long-term occupational exposure may prod TOXICITY IRR	ng difficult breathing and related systemic problems. Juce cumulative health effects involving organs or biochemical systems. ITATION Available
Pola Office Powder	Limited evidence suggests that repeated or long-term occupational exposure may prod TOXICITY IRR Not Available Not A 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value extracted from RTECS - Register of Toxic Effect of chemical Substances	ng difficult breathing and related systemic problems. Juce cumulative health effects involving organs or biochemical systems. ITATION Available
Pola Office Powder Legend:	Limited evidence suggests that repeated or long-term occupational exposure may prod TOXICITY IRRI Not Available Not A 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value extracted from RTECS - Register of Toxic Effect of chemical Substances S Carcino	ng difficult breathing and related systemic problems. fuce cumulative health effects involving organs or biochemical systems. ITATION Available a obtained from manufacturer's SDS. Unless otherwise specified data
Pola Office Powder Legend: Acute Toxicity	Limited evidence suggests that repeated or long-term occupational exposure may prod TOXICITY IRRI Not Available Not A 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value extracted from RTECS - Register of Toxic Effect of chemical Substances S Carcino	ITATION Available a obtained from manufacturer's SDS. Unless otherwise specified data
Pola Office Powder Legend: Acute Toxicity Skin Irritation/Corrosion Serious Eye	Limited evidence suggests that repeated or long-term occupational exposure may prod TOXICITY IRRI Not Available Not A 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value extracted from RTECS - Register of Toxic Effect of chemical Substances Image: Carcino Control of Carcino Control of Carcino Control of Carcino	Ing difficult breathing and related systemic problems. tuce cumulative health effects involving organs or biochemical systems. ITATION Available a obtained from manufacturer's SDS. Unless otherwise specified data ogenicity Suctivity

0

Aspiration Hazard

Legena:

Data available but uses not illi une unterna isi sassification
 Data required to make classification available

🚫 – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

12.1. Toxicity					
Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
Not Available	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

DO NOT discharge into sewer or waterways.

12.2. Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

12.3. Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

12.4. Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

12.5.Results of PBT and vPvB assessment

	Р	В	т
Relevant available data	Not Available	Not Available	Not Available
PBT Criteria fulfilled?	Not Available	Not Available	Not Available

12.6. Other adverse effects

No data available

SECTION 13 DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Product / Packaging disposal	 DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority.
Waste treatment options	Not Available
Sewage disposal options	Not Available

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO		
HAZCHEM	Not Applicable		
Land transport (ADR): NOT	Land transport (ADR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS		
14.1.UN number	Not Applicable		
14.2.Packing group	Not Applicable		
14.3.UN proper shipping name	Not Applicable		
14.4.Environmental hazard	Not Applicable		
14.5. Transport hazard class(es)	Class Not Applicable Subrisk Not Applicable		
14.6. Special precautions for user	Hazard identification (Kemler)Not ApplicableClassification codeNot ApplicableHazard LabelNot ApplicableSpecial provisionsNot Applicable		

Not Applicable

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Limited quantity

14.1. UN number	Not Applicable	
14.2. Packing group	Not Applicable	
14.3. UN proper shipping name	Not Applicable	
14.4. Environmental hazard	Not Applicable	
14.5. Transport hazard class(es)	ICAO/IATA Class Not Applicable ICAO / IATA Subrisk Not Applicable ERG Code Not Applicable	
14.6. Special precautions for user	Special provisions Cargo Only Packing Instructions Cargo Only Maximum Qty / Pack Passenger and Cargo Packing Instructions Passenger and Cargo Maximum Qty / Pack Passenger and Cargo Limited Quantity Packing Instructions Passenger and Cargo Limited Maximum Qty / Pack	Not Applicable Not Applicable Not Applicable Not Applicable Not Applicable Not Applicable

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable		
14.2. Packing group	Not Applicable		
14.3. UN proper shipping name	Not Applicable		
14.4. Environmental hazard	Not Applicable		
14.5. Transport hazard class(es)	IMDG Class Not Applicable IMDG Subrisk Not Applicable		
14.6. Special precautions for user	EMS Number Not Applicable Special provisions Not Applicable Limited Quantities Not Applicable		

Inland waterways transport (ADN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.1. UN number	Not Applicable		
14.2. Packing group	Not Applicable		
14.3. UN proper shipping name	Not Applicable		
14.4. Environmental hazard	Not Applicable		
14.5. Transport hazard class(es)	Not Applicable Not Applicable		
14.6. Special precautions for user	Classification code Not Applicable Special provisions Not Applicable Limited quantity Not Applicable Equipment required Not Applicable Fire cones number Not Applicable		

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

If packed as Chemical kits the following classification may be considered if all ICAO/IATA transport requirements are met: Chemical Kit UN3316 - Class 9.

SECTION 15 REGULATORY INFORMATION

15.1. Safety, health and environmental regulations / legislation specific for the substance or mixture

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable -: 67/548/EEC, 1999/45/EC, 98/24/EC, 92/85/EC, 94/33/EC, 91/689/EEC, 1999/13/EC, Commission Regulation (EU) 2015/830, Regulation (EC) No 1272/2008 and their amendments as well as the following British legislation: - The Control of Substances Hazardous to Health Regulations (COSHH) 2002 - COSHH Essentials - The Management of Health and Safety at Work Regulations 1999

15.2. Chemical safety assessment

For further information please look at the Chemical Safety Assessment and Exposure Scenarios prepared by your Supply Chain if available.

ECHA SUMMARY

National Inventory	Status
Australia - AICS	Υ
Canada - DSL	Υ
Canada - NDSL	Υ
China - IECSC	Υ
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	Υ
Korea - KECI	Υ
New Zealand - NZIoC	Υ
Philippines - PICCS	Υ
USA - TSCA	Υ
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Full text Risk and Hazard codes

Other information

DSD / DPD label elements



Relevant risk statements are found in section 2.1

Indication(s) of danger	Xi	
SAFETY ADVICE		
S02	Keep out of reach of children.	
S26	In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.	
S35	This material and its container must be disposed of in a safe way.	
\$37	Wear suitable gloves.	
S39	Wear eye/face protection.	
S40	To clean the floor and all objects contaminated by this material, use water and detergent.	
S46	If swallowed, seek medical advice immediately and show this container or label.	
S56	Dispose of this material and its container at hazardous or special waste collection point.	

S64 If swallowed, rinse mouth with water (only if the person is conscious).

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by SDI Limited using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection

EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average PC – STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit, IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor NOAEL: No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level LOD: Limit of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

The information contained in the Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be

obtained from the use thereof.

Other information:

Prepared by: SDI Limited 3-15 Brunsdon Street, Bayswater Victoria, 3153, Australia Phone Number: +61 3 8727 7111 Date of preparation/revision: 23rd September 2015 Department issuing SDS: Research and Development Contact: Technical Director

Other information:

Prepared by: SDI Limited 3-15 Brunsdon Street, Bayswater Victoria, 3153, Australia

Phone Number: +61 3 8727 7111

Date of preparation/revision: 23rd September 2015

Department issuing SDS: Research and Development

Contact: Technical Director

