

SDI Limited

Version No: 8.1 Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements Issue Date: 10/03/2023 Print Date: 17/11/2023 L.GHS.AUS.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	Pola Office Plus Ultra 6% hydrogen peroxide
Chemical Name	Not Applicable
Synonyms	Not Available
Chemical formula	Not Applicable
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	To remove discoloration of teeth under the supervision of a dentist.

Details of the manufacturer or supplier of the safety data sheet

Registered company name	SDI Limited	SDI (North America) Inc.	SDI HOLDINGS PTY LTD DO
Address	3-15 Brunsdon Street Bayswater VIC 3153 Australia	1279 Hamilton Parkway Itasca IL 60143 United States	Rua Dr. Reinaldo Schmithausen 3141 – Cordeiros Itajaí – SC – CEP 88310-004 Brazil
Telephone	+61 3 8727 7111	+1 630 361 9200	+55 11 3092 7100
Fax	+61 3 8727 7222	Not Available	Not Available
Website	www.sdi.com.au	www.sdi.com.au	http://www.sdi.com.au/
Email	info@sdi.com.au	USA.Canada@sdi.com.au	Brasil@sdi.com.au
Registered company name	SDI Germany GmbH		
Address	Hansestrasse 85 Cologne D-51149 Germany		
Telephone	+49 0 2203 9255 0		
Fax	+49 0 2203 9255 200		
Website	www.sdi.com.au		
Email	germany@sdi.com.au		

Emergency telephone number

Association / Organisation	SDI Limited	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone numbers	131126 Poisons Information Centre	+61 1800 951 288
Other emergency telephone numbers	+61 3 8727 7111	+61 3 9573 3188

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture		
Poisons Schedule	S5	
Classification [1]	Skin Corrosion/Irritation Category 1A, Serious Eye Damage/Eye Irritation Category 1	
Legend:	1. Classification by vendor; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	

Label elements

Hazard pictogram(s)	
Signal word	Danger

Hazard statement(s)			
H314	Causes severe skin burns and eye damage.		
recautionary statement(s) Pr	avention		
P260	Do not breathe mist/vapours/spray.		
P264	Wash all exposed external body areas thoroughly after ha	-	
P280	Wear protective gloves, protective clothing, eye protection	and face protection.	
Precautionary statement(s) Ro	esponse		
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.		
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminate	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minut	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P310	Immediately call a POISON CENTER/doctor/physician/first aider.		
P363	Wash contaminated clothing before reuse.		
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
Precautionary statement(s) St	orage		
P405	Store locked up.		
Precautionary statement(s) Di	sposal		
P501	Dispose of contents/container to authorised hazardous or	special waste collection point in accordance with any local regulation.	
SECTION 3 Composition / i	nformation on ingredients		
Substances			
See section below for composition	of Mixtures		
Mixtures			
CAS No	%[weight]	Name	

CAS No	%[weight] Name	
7722-84-1	6	hydrogen peroxide
Legend:	1. Classification by vendor; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available	

SECTION 4 First aid measures

Description of first aid measures		
Eye Contact	 If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. 	
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation. 	
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary. 	
Ingestion	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice. 	

Indication of any immediate medical attention and special treatment needed

Hydrogen peroxide at moderate concentrations (5% or more) is a strong oxidant. • Direct contact with the eye is likely to cause corneal damage especially if not washed immediately. Careful ophthalmologic evaluation is recommended and the possibility of local corticosteroid therapy should be considered.

Because of the likelihood of systemic effects attempts at evacuating the stomach via emesis induction or gastric lavage should be avoided.

There is remote possibility, however, that a nasogastric or orogastric tube may be required for the reduction of severe distension due to gas formation" Fisher Scientific SDS

SECTION 5 Firefighting measures

Extinguishing media

- Foam.
- Dry chemical powder.
 BCF (where regulations permit).
 Carbon dioxide.

Water spray or fog - Large fires only.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
Advice for firefighters	

dvice for firefighters	
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use.
Fire/Explosion Hazard	 Non combustible. Not considered a significant fire risk, however containers may burn. May emit poisonous fumes. May emit corrosive fumes. Decomposes on heating and produces: carbon dioxide (CO2) carbon monoxide (CO)
HAZCHEM	Not Applicable

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid contact with skin and eyes. Wear impervious gloves and safety goggles. Trowel up/scrape up. Place spilled material in clean, dry, sealed container. Flush spill area with water.
Major Spills	 Minor hazard. Clear area of personnel. Alert Fire Brigade and tell them location and nature of hazard. Control personal contact with the substance, by using protective equipment as required. Prevent spillage from entering drains or water ways. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Absorb remaining product with sand, earth or vermiculite and place in appropriate containers for disposal. Wash area and prevent runoff into drains or waterways. If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. DO NOT allow material to contact humans, exposed food or food utensils. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
Other information	Store between 2 and 25 deg C. , Do not store in direct sunlight. , Store in a cool dry place.

Conditions for safe storage, including any incompatibilities

•	
Suitable container	DO NOT repack. Use containers supplied by manufacturer only.
Storage incompatibility	Avoid strong bases.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits	(OEL)

INGREDIENT DATA

Ingredient	Material name	TWA		STEL		Peak	Notes
hydrogen peroxide	Hydrogen peroxide	1 ppm / 1.4 mg/r	m3	Not Available		Not Available	Not Available
TEEL-1	TE	EL-2			TEE	L-3	
Not Available	No	t Available			Not	Available	
Original IDLH			Revised	IDLH			
			Not Avai	lable			
	hydrogen peroxide	hydrogen peroxide Hydrogen peroxide TEEL-1 TE Not Available Not Original IDLH Not	hydrogen peroxide Hydrogen peroxide 1 ppm / 1.4 mg/r TEEL-1 TEEL-2 Not Available Not Available Original IDLH	hydrogen peroxide Hydrogen peroxide 1 ppm / 1.4 mg/m3 TEEL-1 TEEL-2 Not Available Not Available Original IDLH Revised	hydrogen peroxide Hydrogen peroxide 1 ppm / 1.4 mg/m3 Not Available TEEL-1 TEEL-2 Not Available Not Available Original IDLH Revised IDLH	TEEL-1 TEEL-2 TEEL Not Available Not Available Not Available Original IDLH Revised IDLH	hydrogen peroxide Hydrogen peroxide 1 ppm / 1.4 mg/m3 Not Available Not Available TEEL-1 TEEL-2 TEEL-3 Not Available Not Available Not Available Original IDLH Revised IDLH

MATERIAL DATA

Exposure controls

Appropriate engineering control Type of Contaminant: Air Speed: solvent, vapours, degreasing etc., evaporating from tank (in still air), 0.25-0.5 mis (50-100 min), accesseds, funes from pouring operations, intermittent container filling, buy speed conveyor transfers, welding, spray 0.5 1 mis (100-200 min), dift, plaining acid funes, picking (released at low velocity) into zone of active generation) 12.5 mis (200-500 min), generation into zone of range ar motion) generation into zone of range ar motion) 12.5 mis (200-500 min), grinding, abreave balangt, turbing, high speed wheel generated dusts (released at high initial velocity into zone of z-10 mis (500-2000 fmin.)) 12.5 mis (200-500 min), Within each range the appropriate value depends on: Lower end of the range Upper end of the range 1. Room air currents minimal of favourable to capture 1. Disturbing room air currents 2. Contaminants of high kostity 2. Lorder hood or large air mass in motion 4. Small hood-local control only Simple theory shows that air velocity falls rangidy with distance ways transfers weaks data from the extraction point bould be adjusted. accordingly, after reference to distance from the contaminating source. The air velocities are multiplied by factors of 10 or more when extraction systems are installed or used. producting performance deficts within the extraction point incluses are sublicated from mechanical considiatatinons, producing performance deficts within the		Engineering controls are used to remove a hazard or place a be highly effective in protecting workers and will typically be it The basic types of engineering controls are: Process controls which involve changing the way a job activit Enclosure and/or isolation of emission source which keeps a "adds" and "removes" air in the work environment. Ventilation ventilation system must match the particular process and che Employers may need to use multiple types of controls to prev Local exhaust ventilation usually required. If risk of overexpo protection. Supplied-air type respirator may be required in sp An approved self contained breathing apparatus (SCBA) may Provide adequate ventilation in warehouse or closed storage velocities which, in turn, determine the "capture velocities" of	ndependent of worker interactions to provide this high level ty or process is done to reduce the risk. selected hazard "physically" away from the worker and vent n can remove or dilute an air contaminant if designed proper emical or contaminant in use. vent employee overexposure. sure exists, wear approved respirator. Correct fit is essential ecial circumstances. Correct fit is essential to ensure adequ y be required in some situations. area. Air contaminants generated in the workplace possess	of protection. tilation that strategically ly. The design of a to obtain adequate ate protection.
Appropriate engineering controls Selection transmission of the stream of the strea		Type of Contaminant:		Air Speed:
Appropriate engineering controls drift, plaking acid turnes, pickling (released at low velocity into zone of active generation) trimin, drift, plaking acid turnes, pickling (released at low velocity into zone of active generation) trimin, 1.2.5 m/s (200-500) generation in zone of rapid air motion) generation in zone of rapid air motion) generation in zone of rapid air motion) 2.5-10 m/s Within each range the appropriate value depends on: Lower end of the range Upper end of the range 2.5-10 m/s 1. Room air currents minimal of ravourable to capture 1: Disturbing room air currents 2.5-00 m/ms (500-2000 fmin.) 3. Intermittent, low production. 3: High production, heavy use 3. High production, heavy use 3. High production, heavy use 4. Large hood or large air mass in motion 4: Small hood-local control only Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction appartus, make it essential that theoretical air velocity after reference to classinate from the contaminating source. The air velocity after serverise, should be a adjusted, accordingly, after reference to distance from the contaminating source. The air velocity after serverise, should be and inturne of 1.2 m/s (200-400 fmin) for extraction spartus, make it essential that theoretical air velocity are multiplied by factors of 10 or more when extraction systems are installed or used. reference <th></th> <td>solvent, vapours, degreasing etc., evaporating from tank (i</td> <td>n still air).</td> <td></td>		solvent, vapours, degreasing etc., evaporating from tank (i	n still air).	
Individual protection Safety glasses with side shields. Contact lenses may passob a special basid. Safety glasses with side shields. Safety glasses with side shields. Contact lenses may passob a special basid. Contact lenses may passob and concentrate infrants. A written policy document, descripting the extraction paint. Contact lenses may passob and concentrate infrants. A written policy document, descripting the extraction patient was and an account of miny experimence. Contact lenses may passob and concentrate infrants. A written policy document, descripting the extraction point during the entracted of the special based based may passob and concentrate infrants. A written policy document, descripting the washed based band concentrate infrants. A written policy document, descripting th				
wery high rapid air motion). (500-2000 f/min.) Within each range the appropriate value depends on: Upper end of the range (500-2000 f/min.) Lower end of the range Upper end of the range (500-2000 f/min.) 2. Contaminants of low toxicity or of nuisance value only. 2. Contaminants of high toxicity 3. Intermittent, low production. 3. High production, heavy use 4. Large hood or large air mass in motion 4. Small hood-local control only Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple attentation pipe. Velocity generally decreases with the square of distance from the extraction pipe. Velocity generally decreases with the square of distance from the extraction pipe. Velocity general de a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction pipe. Velocity general de a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction pipe. Velocity general decination point (1) minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction pipe. Velocity generally decreases with set sensitil for the extraction pipe. Velocity generally decreases protectical are velocity at the extraction pipe. Velocity generally decreases protectical performance deficits within the extraction approximate of tanks are installed or used. Individual protection Safety glasses with side shields. Events distant from the extraction pipe. Velocity generally decreases are installed or used.	controls		conveyer loading, crusher dusts, gas discharge (active	
Lower end of the range Upper end of the range 1: Room air currents minimal or favourable to capture 1: Disturbing room air currents 2: Contaminants of low toxicity or of nuisance value only. 2: Contaminants of high toxicity 3: Intermittent, low production. 3: High production, heavy use 4: Large hood or large air mass in motion 4: Small hood-local control only Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreaseses with the square of distance from the extraction pipe in simple cases). Therefore the air speed at the extraction pipe, should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction pipe, should be adjusted, second producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used. Eye and face protection protection Safety glasses with side shields. Contract lenses may pose a special hazard, soft contact lenses may absorb and concentrate iritants. A written policy document, describing the wearing of lenses or restrictions on use, should be ready available. In the create or task. This should be trained in their removal and assorption of the class of chemicals in use and an account of luiny experience. Medical and first-aid personel should be trained in their removal and assorption of the class of chemicals in use and an account of high yes preferees. Medical and first-aid personel should be trainded in their removal and suitable equipment should be r			nerated dusts (released at high initial velocity into zone of	
1: Room air currents minimal or favourable to capture 1: Disturbing room air currents 2: Contaminants of low toxicity or of nuisance value only. 2: Contaminants of high toxicity 3: Intermittent, low production. 3: High production, heavy use 4: Large hood or large air mass in motion 4: Small hood-local control only Simple theory shows that air velocity falls rapidly with distance away from the opening of a single extraction point ishould be adjusted, accordingly, after reference to distance from the extraction point in single cases). Therefore the air speed at the extraction point, of the away to a single extraction point. Other metanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used. Eye and face protection measures, such as personal protective equipment 2: Affety glasses with side shields. Eye and face protection 2: Affety glasses with side shields. Eye and face protection 2: Affety glasses with side shields. String protection 2: Affety glasses with side shields. String to extract the extraction son use, should be ready available or task. This should include a review of lens absorption and adsorption for the class of chericals in use and an account of injury experience. Medical and first-aid personnel should be removed in a clean environment only after workers have washed hands thoroughly. (ICDC NIOSH Current Intelligence Bulletin 59). Skin protection		Within each range the appropriate value depends on:		
2: Contaminants of low toxicity or of nuisance value only. 2: Contaminants of high toxicity 3: Intermittent, low production. 3: High production, heavy use 4: Large hood or large air mass in motion 4: Small hood-local control only Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction point should be adjusted, accordingly, after reference to distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used. Individual protection measures, such as personal protective equipment Safety glasses with side shields. Chemical goggles. [ASh/AZS 1337.1, EN166 or national equivalent] Contact lenses may pose a special hazard; soft contable create dor each workplace or task. This should include a review of lens assorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and their removal and		Lower end of the range	Upper end of the range	
3: Intermittent, low production. 3: High production, heavy use 4: Large hood or large air mass in motion 4: Small hood-local control only Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (In simple cases). Therefore the air speed at the extraction point should be a minimum of 1-2 m/s (200-400 fmin) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used. Individual protection generation and the specific within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used. Eye and face protection Safety glasses with side shields. Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent] Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the waring of lenses or restrictions on use, should be readiva available. In the event of chemical exposure, begin eye irrigation immediately and their removal and suitable equipment should be readival available. In the event of chemical exposure, begin eye irrigation immediately and their removal and suitable equipment should be readival available. In the event of chemical exposure, begin eye irrigation immediately and their removal and suitable equipment should be removed at the first signs of eye refness or irristrico		1: Room air currents minimal or favourable to capture	1: Disturbing room air currents	
4: Large hood or large air mass in motion 4: Small hood-local control only Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction point. Other mechanical considerations, producing performance deficits within the extraction point (in simple cases). Therefore the air speed at the extraction point. Other mechanical considerations, producing performance deficits within the extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used. Individual protection measures, such as personal protective equipment Safety glasses with side shields. Chemical goggles, IAS/NZS 1337.1, EN166 or national equivalent] Contact lenses may base a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the waring of lenses or restrictions on use, should be reated for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be reatived in their removal and suitable equipment should be reative and account of injury experience. Medical and first-aid personnel should be removed in a clean environment only after workers have washed hands thoroughly. (CDC NIOSH Current Intelligence Bulletin 59). Skin protection See Hand protection pelow Hands/feet protection Wear chemical protecive gloves, e.g., PVC.		2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity	
Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction point should be adjusted, accordingly, after reference to distance from the contaminanting source. The air velocity at the extraction point should be adjusted, accordingly, after reference to distance from the contaminanting source. The air velocity at the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used. Individual protection measures, such as personal protective equipment Image: Contact Conta		3: Intermittent, low production.	3: High production, heavy use	
with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 2 m/s (20-400 f/min) for extraction of solvents generated in a tax 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used. Individual protection measures, such as personal protective equipment Image: Construction of Construction of Construction (Construction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used. Eye and face protection Safety glasses with side shields. Image: Construction of Construction on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemical equivalent] Contact lenses may pose a special hazard, soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59]. Skin protection See Hand pro		4: Large hood or large air mass in motion	4: Small hood-local control only	
measures, such as personal protective equipment • Safety glasses with side shields. • Safety glasses with side shields. • Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent] • Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59]. Skin protection See Hand protection below • Wear chemical protective gloves, e.g. PVC. • Wear safety footwear or safety gumboots, e.g. Rubber • Rubber Gloves		with the square of distance from the extraction point (in simpl accordingly, after reference to distance from the contaminatin 1-2 m/s (200-400 f/min) for extraction of solvents generated in producing performance deficits within the extraction apparatu	le cases). Therefore the air speed at the extraction point sho ng source. The air velocity at the extraction fan, for example, n a tank 2 meters distant from the extraction point. Other me	ould be adjusted, should be a minimum of echanical considerations,
Eye and face protection Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent] Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59]. Skin protection See Hand protection below 	measures, such as personal			
Hands/feet protection Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber Rubber Gloves Rubber Gloves	Eye and face protection	 Chemical goggles. [AS/NZS 1337.1, EN166 or national e Contact lenses may pose a special hazard; soft contact l the wearing of lenses or restrictions on use, should be or and adsorption for the class of chemicals in use and an their removal and suitable equipment should be readily a remove contact lens as soon as practicable. Lens should 	enses may absorb and concentrate irritants. A written policy reated for each workplace or task. This should include a revi account of injury experience. Medical and first-aid personnel available. In the event of chemical exposure, begin eye irriga I be removed at the first signs of eye redness or irritation - le	ew of lens absorption should be trained in tion immediately and ens should be removed in
Hands/feet protection Wear safety footwear or safety gumboots, e.g. Rubber Rubber Gloves Rubber Gloves	Skin protection	See Hand protection below		
Body protection See Other protection below	Hands/feet protection	Wear safety footwear or safety gumboots, e.g. Rubber		
	Body protection	See Other protection below		

Other protection	 Overalls. P.V.C apron. Barrier cream. Skin cleansing cream. Eye wash unit.
------------------	--

Respiratory protection

Type B Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	B-AUS	-	B-PAPR-AUS / Class 1
up to 50 x ES	-	B-AUS / Class 1	-
up to 100 x ES	-	B-2	B-PAPR-2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Clear blue gel with no odour, mixes with water.		
Physical state	Gel	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Applicable	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an
Ingestion	occupational setting. The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.
Skin Contact	Limited evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four

	redness (erythema) and swelling (oedema) which may pro microscopic level there may be intercellular oedema of the Open cuts, abraded or irritated skin should not be exposed	rasions, puncture wounds or lesions, may produce systemic injury with harmful effe
Eye	Evidence exists, or practical experience predicts, that the r produce significant ocular lesions which are present twenty	material may cause eye irritation in a substantial number of individuals and/or may y-four hours or more after instillation into the eye(s) of experimental animals. on characterised by temporary redness (similar to windburn) of the conjunctiva
Chronic	Limited evidence suggests that repeated or long-term occubiochemical systems.	upational exposure may produce cumulative health effects involving organs or
Pola Office Plus Ultra 6%	тохісіту	IRRITATION
hydrogen peroxide	Not Available	Not Available
	тохісіту	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Not Available
hydrogen peroxide	Inhalation(Mouse) LC50; 2800 mg/L4h ^[2]	
hydrogen peroxide	Inhalation(Mouse) LC50; 2800 mg/L4h ^[2] Oral (Rat) LD50: >225 mg/kg ^[2]	

Carolingenery F1	chicken eggs on day 3 of incubation. Embryos were examined on day 14. The incidence of embryonic deaths and malformations was dose-related and d mol/egg and above. The combined ED50 was 2.7 mol/egg. Reproductive Toxicity A 1% solution of hydrogen peroxide (equivalent to 1900 mg/kg/day) given as the sole drinking fluid to three-month-c did not cause infertility. The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.	
		nicity X
Skin Irritation/Corrosion		nicity X

Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×
		Legend: X – Data either not available or does not fill the criteria for classification - Data available to make classification	

SECTION 12 Ecological information

Toxicity

Pola Office Plus Ultra 6% hydrogen peroxide	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	0.69mg/l	4
1	EC50	48h	Crustacea	2mg/l	2
hydrogen peroxide	EC50	96h	Algae or other aquatic plants	2.27mg/l	4
	NOEC(ECx)	72h	Algae or other aquatic plants	0.1mg/l	1
	LC50	96h	Fish	16.4mg/l	2

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
hydrogen peroxide	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
hydrogen peroxide	LOW (LogKOW = -1.571)
Mahility in anil	
Mobility in soil	
Ingredient	Mobility
hydrogen peroxide	LOW (KOC = 14.3)

SECTION 13 Disposal considerations

Waste treatment methods		
	Consult State Land Waste Management Authority for disposal. Bury residue in an authorised landfill.	

SECTION 14 Transport information

Labels Required		
Marine Pollutant	NO	
HAZCHEM	Not Applicable	

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
hydrogen peroxide	Not Available
14.7.3. Transport in bulk in accordance with the IGC Code	

Product name	Ship Type
hydrogen peroxide	Not Available

Safety, health and environmental regulations / legislation specific for the substance or mixture

hydrogen peroxide is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

- Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) Schedule 10 / Appendix C
- Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) Schedule 5
- Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) Schedule 6

Australian Inventory of Industrial Chemicals (AIIC)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (hydrogen peroxide)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	10/03/2023
Initial Date	09/11/2015

SDS Version Summary

Version	Date of Update	Sections Updated
7.1	23/12/2022	Classification review due to GHS Revision change.
8.1	10/03/2023	Classification change due to full database hazard calculation/update.

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by SDI Limited using available literature references

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- PC TWA: Permissible Concentration-Time Weighted Average
- PC STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit.
- IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors Þ
- BEI: Biological Exposure Index DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
- AIIC: Australian Inventory of Industrial Chemicals
- ٠ DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- IECSC: Inventory of Existing Chemical Substance in China
- EINECS: European INventory of Existing Commercial chemical Substances

Continued...

- ▶ ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
 INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- + FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

The information contained in the Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.

Other information:

Prepared by: SDI Limited 3-15 Brunsdon Street, Bayswater Victoria, 3153, Australia Phone Number: +61 3 8727 7111 Department issuing SDS: Research and Development Contact: Technical Director

