

SDI Limited Version No: 11.1

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

Issue Date: **10/03/2023** Print Date: **17/11/2023** L.GHS.AUS.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

| Product Identifier | |
|-------------------------------|---------------------------|
| Product name | Riva Luting Plus (liquid) |
| Chemical Name | Not Applicable |
| Synonyms | Not Available |
| Chemical formula | Not Applicable |
| Other means of identification | Not Available |

Relevant identified uses of the substance or mixture and uses advised against

| Relevant identified uses | Professional dental use: Liquid for dental restorative cement. |
|--------------------------|--|
| | |

Details of the manufacturer or supplier of the safety data sheet

| Registered company name | SDI Limited | SDI (North America) Inc. | SDI Germany GmbH |
|-------------------------|---|---|---|
| Address | 3-15 Brunsdon Street Bayswater VIC 3153 Australia | 1279 Hamilton Parkway Itasca IL 60143 United States | Hansestrasse 85 Cologne D-51149 Germany |
| Telephone | +61 3 8727 7111 | +1 630 361 9200 | +49 0 2203 9255 0 |
| Fax | +61 3 8727 7222 | Not Available | +49 0 2203 9255 200 |
| Website | www.sdi.com.au | www.sdi.com.au | www.sdi.com.au |
| Email | info@sdi.com.au | USA.Canada@sdi.com.au | germany@sdi.com.au |
| Registered company name | SDI HOLDINGS PTY LTD DO | | |
| Address | Rua Dr. Reinaldo Schmithausen 3141 – Cordeiros Itajaí – SC – CEP 88310-004 Brazil | | |
| Telephone | +55 11 3092 7100 | | |
| Fax | Not Available | | |
| Website | http://www.sdi.com.au/ | | |
| Email | Brasil@sdi.com.au | | |

Emergency telephone number

| Association / Organisation | SDI Limited | CHEMWATCH EMERGENCY RESPONSE (24/7) |
|-----------------------------------|-----------------------------------|-------------------------------------|
| Emergency telephone numbers | 131126 Poisons Information Centre | +61 1800 951 288 |
| Other emergency telephone numbers | +61 3 8727 7111 | +61 3 9573 3188 |

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

| Poisons Schedule | Not Applicable |
|-------------------------------|---|
| Classification ^[1] | Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 2, Sensitisation (Skin) Category 1A, Serious Eye Damage/Eye Irritation Category 2A, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Carcinogenicity Category 1B, Specific Target Organ Toxicity - Repeated Exposure Category 2, Hazardous to the Aquatic Environment Long-Term Hazard Category 4 |
| Legend: | 1. Classification by vendor; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI |

Label elements

Hazard pictogram(s)

Signal word Danger

Hazard statement(s)

| H302 | Harmful if swallowed. |
|------|--|
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |
| H335 | May cause respiratory irritation. |
| H350 | May cause cancer. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H413 | May cause long lasting harmful effects to aquatic life. |

Precautionary statement(s) Prevention

| P201 | Obtain special instructions before use. |
|------|--|
| P260 | Do not breathe mist/vapours/spray. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P280 | Wear protective gloves, protective clothing, eye protection and face protection. |
| P264 | Wash all exposed external body areas thoroughly after handling. |
| P270 | Do not eat, drink or smoke when using this product. |
| P273 | Avoid release to the environment. |
| P272 | Contaminated work clothing should not be allowed out of the workplace. |

Precautionary statement(s) Response

| P308+P313 | IF exposed or concerned: Get medical advice/ attention. | |
|----------------|--|--|
| P302+P352 | IF ON SKIN: Wash with plenty of water. | |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. | |
| P333+P313 | If skin irritation or rash occurs: Get medical advice/attention. | |
| P337+P313 | If eye irritation persists: Get medical advice/attention. | |
| P362+P364 | Take off contaminated clothing and wash it before reuse. | |
| P301+P312 | IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell. | |
| P304+P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. | |
| P330 | Rinse mouth. | |

Precautionary statement(s) Storage

| P405 | Store locked up. |
|-----------|--|
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |

Precautionary statement(s) Disposal

P501

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

| CAS No | %[weight] | Name |
|------------|---|---------------------------------------|
| 868-77-9 | 10-25 | 2-hydroxyethyl methacrylate |
| 52628-03-2 | 15-20 | 2-hydroxyethyl methacrylate phosphate |
| 9003-01-4 | 5-15 | acrylic acid homopolymer |
| 1830-78-0 | 5-10 | glycerol dimethacrylate |
| 87-69-4 | 1-5 | tartaric acid |
| Legend: | Classification by vendor; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available | |

SECTION 4 First aid measures

| Description of first aid measures | | |
|-----------------------------------|--|--|
| Eye Contact | If this product comes in contact with eyes: Wash out immediately with water. If irritation continues, seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. | |
| Skin Contact | If skin or hair contact occurs: ► Flush skin and hair with running water (and soap if available). ► Seek medical attention in event of irritation. | |

Issue Date: 10/03/2023 Print Date: 17/11/2023

| Inhalation | If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay. |
|------------|--|
| Ingestion | Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. Seek medical attention. |

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog Large fires only.

| Special hazards arising from the substrate or mixture | | |
|---|---|--|
| Fire Incompatibility | None known. | |
| Advice for firefighters | | |
| Fire Fighting | Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water courses. Use water delivered as a fine spray to control fire and cool adjacent area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use. | |
| Fire/Explosion Hazard | Combustible. Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit toxic fumes of carbon monoxide (CO). May emit acrid smoke. Mists containing combustible materials may be explosive. Combustion products include: carbon dioxide (CO2) other pyrolysis products typical of burning organic material. May emit corrosive fumes. May emit corrosive fumes. | |
| HAZCHEM | Not Applicable | |

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

| Minor Spills | Clean up all spills immediately. Avoid contact with skin and eyes. Wear impervious gloves and safety goggles. Trowel up/scrape up. Place spilled material in clean, dry, sealed container. Flush spill area with water. |
|--------------|--|
| Major Spills | Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Neutralise/decontaminate residue (see Section 13 for specific agent). Collect solid residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains. After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using. If contamination of drains or waterways occurs, advise emergency services. |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

| Precautions for safe handling | |
|-------------------------------|---|
| Safe handling | Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. DO NOT allow material to contact humans, exposed food or food utensils. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained. |
| Other information | Store in a dry and well ventilated-area, away from heat and sunlight. Store between 5 and 25 deg. C. |

Conditions for safe storage, including any incompatibilities

| Suitable container | DO NOT repack. Use containers supplied by manufacturer only. Check that containers are clearly labelled and free from leaks |
|-------------------------|--|
| Storage incompatibility | Avoid strong bases. |

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

Emergency Limits

| Ingredient | TEEL-1 | TEEL-2 | | TEEL-3 |
|---------------------------------------|---------------|----------|---------------|-------------|
| 2-hydroxyethyl methacrylate | 1.9 mg/m3 | 21 mg/m3 | | 1,000 mg/m3 |
| tartaric acid | 1.6 mg/m3 | 17 mg/m3 | | 100 mg/m3 |
| Ingredient | Original IDLH | | Revised IDLH | |
| 2-hydroxyethyl methacrylate | Not Available | | Not Available | |
| 2-hydroxyethyl methacrylate phosphate | Not Available | | Not Available | |
| acrylic acid homopolymer | Not Available | | Not Available | |
| glycerol dimethacrylate | Not Available | | Not Available | |
| tartaric acid | Not Available | | Not Available | |

| Occupational Exposure Banding | | |
|--|--|----------------------------------|
| Ingredient | Occupational Exposure Band Rating | Occupational Exposure Band Limit |
| 2-hydroxyethyl methacrylate | E | ≤ 0.1 ppm |
| 2-hydroxyethyl methacrylate phosphate | E | ≤ 0.1 ppm |
| acrylic acid homopolymer | E | ≤ 0.01 mg/m³ |
| glycerol dimethacrylate | E | ≤ 0.1 ppm |
| tartaric acid | E | ≤ 0.01 mg/m³ |
| Notes: | Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health. | |

MATERIAL DATA

NOTE D: Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed on Annex I

When they are placed on the market in a non-stabilised form, the label must state the name of the substance followed by the words "non-stabilised" European Union (EU) List of harmonised classification and labelling hazardous substances, Table 3.1, Annex VI, Regulation (EC) No 1272/2008 (CLP) - up to the latest ATP

Exposure controls

| Appropriate engineering controls | CARE: Use of a quantity of this material in confined space or poorly ventilated area, where rapid build up of concentrated atmosphere may occur, could require increased ventilation and/or protective gear Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. | | | |
|-------------------------------------|--|--|--|--|

| | Employers may need to use multiple types of controls to prevent employee overexposure. | | |
|---|--|---|--|
| | Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection. An approved self contained breathing apparatus (SCBA) may be required in some situations. Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant. | | |
| | Type of Contaminant: | | Air Speed: |
| | solvent, vapours, degreasing etc., evaporating from tank (in still air). | | |
| | aerosols, fumes from pouring operations, intermittent conta drift, plating acid fumes, pickling (released at low velocity in | | 0.5-1 m/s (100-200 f/min.) |
| | direct spray, spray painting in shallow booths, drum filling, generation into zone of rapid air motion) | conveyer loading, crusher dusts, gas discharge (active | 1-2.5 m/s (200-500 f/min.) |
| | grinding, abrasive blasting, tumbling, high speed wheel gen very high rapid air motion). | nerated dusts (released at high initial velocity into zone of | 2.5-10 m/s (500-2000 f/min.) |
| | Within each range the appropriate value depends on: | | |
| | Lower end of the range | Upper end of the range | |
| | 1: Room air currents minimal or favourable to capture | 1: Disturbing room air currents | |
| | 2: Contaminants of low toxicity or of nuisance value only. | 2: Contaminants of high toxicity | |
| | 3: Intermittent, low production. | 3: High production, heavy use | |
| | 4: Large hood or large air mass in motion | 4: Small hood-local control only | |
| | Simple theory shows that air velocity falls rapidly with distance with the square of distance from the extraction point (in simpl accordingly, after reference to distance from the contaminatin 1-2 m/s (200-400 f/min) for extraction of solvents generated i producing performance deficits within the extraction apparatu more when extraction systems are installed or used. | le cases). Therefore the air speed at the extraction point sho ng source. The air velocity at the extraction fan, for example n a tank 2 meters distant from the extraction point. Other mo | buld be adjusted, , should be a minimum of echanical considerations, |
| Individual protection measures, such as personal protective equipment | | | |
| Eye and face protection | Safety glasses with side shields. Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent] Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59]. | | |
| Skin protection | See Hand protection below | | |
| Hands/feet protection | Rubber Gloves Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber | | |
| Body protection | See Other protection below | | |
| Other protection | No special equipment needed when handling small quantities OTHERWISE: • Overalls. • Barrier cream. • Eyewash unit. | 5. | |

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

| Required minimum protection factor | Maximum gas/vapour concentration present in air p.p.m. (by volume) | Half-face Respirator | Full-Face Respirator |
|------------------------------------|--|----------------------|----------------------|
| up to 10 | 1000 | A-AUS / Class1 P3 | - |
| up to 50 | 1000 | - | A-AUS / Class 1 P3 |
| up to 50 | 5000 | Airline * | - |
| up to 100 | 5000 | - | A-2 P3 |
| up to 100 | 10000 | - | A-3 P3 |
| 100+ | | | Airline** |

* - Continuous Flow ** - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 Physical and chemical properties

| Appearance | Slightly yellow liquid with slight characteristic odour, mixes with water. | | |
|---|--|---|----------------|
| Physical state | Liquid | Relative density (Water = 1) | Not Available |
| Odour | Not Available | Partition coefficient n-octanol / water | Not Available |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | Not Available |
| pH (as supplied) | <2 | Decomposition temperature (°C) | Not Available |
| Melting point / freezing point (°C) | Not Available | Viscosity (cSt) | Not Available |
| Initial boiling point and boiling range (°C) | Not Available | Molecular weight (g/mol) | Not Applicable |
| Flash point (°C) | Not Available | Taste | Not Available |
| Evaporation rate | Not Available | Explosive properties | Not Available |
| Flammability | Not Available | Oxidising properties | Not Available |
| Upper Explosive Limit (%) | Not Available | Surface Tension (dyn/cm or mN/m) | Not Available |
| Lower Explosive Limit (%) | Not Available | Volatile Component (%vol) | Not Available |
| Vapour pressure (kPa) | Not Available | Gas group | Not Available |
| Solubility in water | Miscible | pH as a solution (1%) | Not Available |
| Vapour density (Air = 1) | Not Available | VOC g/L | Not Available |

SECTION 10 Stability and reactivity

| Reactivity | See section 7 |
|-------------------------------------|---|
| Chemical stability | Product is considered stable and hazardous polymerisation will not occur. |
| Possibility of hazardous reactions | See section 7 |
| Conditions to avoid | See section 7 |
| Incompatible materials | See section 7 |
| Hazardous decomposition products | See section 5 |

SECTION 11 Toxicological information

Information on toxicological effects

| Information on toxicological ef | flects |
|---------------------------------|--|
| Inhaled | Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system. Inhalation hazard is increased at higher temperatures. Acute effects from inhalation of high concentrations of vapour are pulmonary irritation, including coughing, with nausea; central nervous system depression - characterised by headache and dizziness, increased reaction time, fatigue and loss of co-ordination |
| Ingestion | Accidental ingestion of the material may be damaging to the health of the individual. |
| Skin Contact | Evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis. The material may accentuate any pre-existing dermatitis condition Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. |
| Eye | Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur. |
| Chronic | Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems. Practical experience shows that skin contact with the material is capable either of inducing a sensitisation reaction in a substantial number of individuals, and/or of producing a positive response in experimental animals. Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological, irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even to tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance who are likely to become hyper-responsive. Substances than can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing air-way hyper-responsiveness. The latter substances are not classified as asthmagens or respiratory sensitisers Wherever it is reasonably practicable, exposure to substances that can cuase occupational asthma should be prevented. Where this is not possible the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health |
| | |

| | Limited evidence suggests that repeated or long-term occu biochemical systems. Sensitisation may give severe responses to very low levels | upational exposure may produce cumulative health effects involving organs or s of exposure, in situations where exposure may occur. |
|----------------------------|---|--|
| | TOXICITY IRRITATION | |
| Riva Luting Plus (liquid) | Not Available | Not Available |
| | ΤΟΧΙΟΙΤΥ | IRRITATION |
| | Dermal (rabbit) LD50: >3000 mg/kg ^[2] | Eye (rabbit): SEVERE *post-exposure |
| -hydroxyethyl methacrylate | Oral (Rat) LD50: >=2000 mg/kg ^[1] | Eye: adverse effect observed (irritating) ^[1] |
| | | Skin (rabbit): non-irritating* * Rohm & Haas |
| | | Skin: no adverse effect observed (not irritating) ^[1] |
| | ΤΟΧΙΟΙΤΥ | IRRITATION |
| -hydroxyethyl methacrylate | Oral (Rat) LD50: >2000 mg/kg ^[1] | Eye: adverse effect observed (irritating) ^[1] |
| phosphate | | Skin: adverse effect observed (corrosive) ^[1] |
| | | Skin: no adverse effect observed (not irritating) $\ensuremath{\left[1\right]}$ |
| | ΤΟΧΙΟΙΤΥ | IRRITATION |
| | Dermal (rabbit) LD50: >2000 mg/kg ^[1] | Eye: adverse effect observed (irreversible damage) ^[1] |
| acrylic acid homopolymer | Inhalation(Rat) LC50: >5.1 mg/l4h ^[1] | Skin: no adverse effect observed (not irritating) ^[1] |
| | Oral (Rat) LD50: 146-468 mg/kg ^[1] | |
| | τοχιζιτγ | IRRITATION |
| glycerol dimethacrylate | Not Available | Not Available |
| | τοχιζιτγ | IRRITATION |
| tartaric acid | dermal (rat) LD50: >2000 mg/kg ^[1] | Not Available |
| | Oral (Rat) LD50: >=2000<=5000 mg/kg ^[1] | |

| 2-HYDROXYETHYL METHACRYLATE | Dermal (rabbit): >5000 mg/kg* Effects persist beyond 21 days |
|---|--|
| 2-HYDROXYETHYL METHACRYLATE PHOSPHATE | No significant acute toxicological data identified in literature search. |
| ACRYLIC ACID HOMOPOLYMER | Polycarboxylates are of low toxicity by all exposure routes examined. Homopolymers(P-AA) are of low acute toxicity to the rat (LD50 > 5 g/kg bw/d) and are not irritating to the rabbit s skin and, at the most, slightly irritating to the eye. Further P-AA has no sensitising potential. The adverse effect after repeated inhalation dosing (91-d/rat) was a mild, reversible pulmonary irritation. This effect is considered as not substance related owing to the physical property of the respirable dust, which caused local and not systemic lung effects. There was neither evidence for a genotoxic potential of PAA using a variety of genetic endpoints in-vitro and in-vivo, nor for developmental toxicity or reprotoxicity in the rat. Based upon the available data, it is considered that exposure to polycarboxylates does not imply any particular hazard to humans The Cosmetic Ingredient Review (CIR) Expert Panel noted that these crosslinked alkyl acrylates are macromolecules that are not expected to pass through the stratum comeum of the skin, so significant dermal absorption is not expected. Therefore, topically applied cosmetics are not expected to result in systemic or reproductive and developmental toxicity or to have genotoxic or caroinogenic effects. upon use. The Panel noted that cosmetic products containing these ingredients are reportedly used around the eyes, on the lips, and on other mucous membranes. Thus, crosslinked alkyl acrylates could be absorbed systemically through the relatively martatum cornea of the conjunctiva, lips, and other mucous membranes, and through ingestion when applied to the lips. However, the Panel noted that any absorption through healthy inature mucous membranes is likely to be not significant.primarily because of the relatively large molecular sizes. Furthermore, the chemically inert nature of the polymers recludes degradation to smaller absorbable species. Absorption of the polymers are used in cosmetics and emulsifying agents at concentrations up to 50%. Acute oral animal stu |

| | crosspolymer, up to 2.5% aq. acrylates/vinyl isodecanoate crosspolymer, 1% aq. dilutions of formulations containing 2% acrylates/vinyl neodecanoate crosspolymer, and formulations containing up to 2.6% lauryl methacrylate/glycol dimethacrylate crosspolymers do not indicate any dermal irritation or sensitization. The only exception was a weak irritant response noted during an intensified Shelanski human repeated insult patch test (HRIPT) with undiluted acrylates/C10-30 alkyl acrylate crosspolymer. Alternative test methods for ocular irritation indicated that acrylates/vinyl isodecanoate crosspolymer and a formulation containing 1% lauryl methacrylate/glycol dimethacrylate crosspolymer are not likely ocular irritants. In studies using rabbits, undiluted acrylates/C10-30 alkyl acrylate crosspolymer produced minimal to moderate irritation, and it was considered a borderline irritant in unrinsed rabbit eyes. Acrylates crosspolymer, at 50% in olive oil, and sodium acrylates crosspolymer-2 did not appear to be ocular irritatis in rabbit eyes. Two different risk assessments evaluating the carcinogenic endpoint for benzene that may be present in acrylates/C10-30 alkyl acrylates crosspolymer resulted in different lifetime risk. One found that the risk was within the range associated with a 10exp 6 cancer risk, while the other reported a 20-fold greater risk. Final Safety Assessment: Crosslinked Alkyl Acrylates as Used in Cosmetics. Nov 2011 Cosmetic Ingredient Review (CIR) Expert Panel http://ntp.niehs.nih.gov/ntp/roc/nominations/2013/publiccomm/attachmentcir_508.pdf The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing. |
|---|--|
| GLYCEROL DIMETHACRYLATE | UV (ultraviolet)/ EB (electron beam) acrylates are generally of low toxicity UV/EB acrylates are divided into two groups; "stenomeric" and "eurymeric" acrylates. The first group consists of well-defined acrylates which can be described by a simple idealised chemical; they are low molecular weight species with a very narrow weight distribution profile. The eurymeric acrylates cannot be described by an idealised structure and may differ fundamentally between various suppliers; they are of relatively high molecular weigh and possess a wide weight distribution. Stenomeric acrylates are usually more hazardous than the eurymeric substances. Stenomeric acrylates are also well defined which allows comparison and exchange of toxicity data - this allows more accurate classification. The stenomerics cannot be classified as a group; they exhibit substantial variation. The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis. |
| TARTARIC ACID | Convulsions, haemorrhage recorded. Convulsions, haem |
| 2-HYDROXYETHYL METHACRYLATE & 2-HYDROXYETHYL METHACRYLATE PHOSPHATE | The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested. |
| 2-HYDROXYETHYL METHACRYLATE & 2-HYDROXYETHYL METHACRYLATE | Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible |

PHOSPHATE & ACRYLIC ACID airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal HOMOPOLYMER & lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to GLYCEROL the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a **DIMETHACRYLATE &** result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The TARTARIC ACID disorder is characterized by difficulty breathing, cough and mucus production. Where no "official" classification for acrylates and methacrylates exists, there has been cautious attempts to create classifications in the absence of contrary evidence. For example Monalkyl or monoarylesters of acrylic acids should be classified as R36/37/38 and R51/53 2-HYDROXYETHYL Monoalkyl or monoaryl esters of methacrylic acid should be classified as R36/37/38 METHACRYLATE Based on the available oncogenicity data and without a better understanding of the carcinogenic mechanism the Health and Environmental **PHOSPHATE & GLYCEROL** Review Division (HERD), Office of Toxic Substances (OTS), of the US EPA previously concluded that all chemicals that contain the acrylate or DIMETHACRYLATE methacrylate moiety (CH2=CHCOO or CH2=C(CH3)COO) should be considered to be a carcinogenic hazard unless shown otherwise by adequate testing This position has now been revised and acrylates and methacrylates are no longer de facto carcinogens -~ Acute Toxicity Carcinogenicity -× Skin Irritation/Corrosion Reproductivity Serious Eye Damage/Irritation ~ STOT - Single Exposure ~ Respiratory or Skin -STOT - Repeated Exposure ~ sensitisation Mutagenicity × Aspiration Hazard × Legend: X - Data either not available or does not fill the criteria for classification

🖌 – Data available to make classification

SECTION 12 Ecological information

Toxicity Endpoint Test Duration (hr) Species Value Source **Riva Luting Plus (liquid)** Not Not Not Not Available Not Available Available Available Available Endpoint Test Duration (hr) Species Value Source EC50 72h Algae or other aquatic plants 345mg/l 2 380mg/l 48h Crustacea 2 2-hydroxyethyl methacrylate EC50 NOEC(ECx) 504h Crustacea 24.1mg/l 2 LC50 >100mg/l 2 Fish 96h Test Duration (hr) Value Endpoint Species Source LC50 96h Fish >112mg/l 2 2-hydroxyethyl methacrylate EC50 72h Algae or other aquatic plants >120mg/l 2 phosphate EC50 48h Crustacea 68mg/l 2 NOEC(ECx) 72h Algae or other aquatic plants >=30mg/l 2 Endpoint Test Duration (hr) Species Value Source EC50 72h Algae or other aquatic plants 0.13-0.205mg/l 2 48h acrylic acid homopolymer EC50 Crustacea 47ma/l 2 EC10(ECx) 72h Algae or other aquatic plants 0.03-0.031mg/l 2 2 LC50 96h Fish 27mg/l Test Duration (hr) Endpoint Species Value Source glycerol dimethacrylate Not Not Not Not Available Not Available Available Available Available Test Duration (hr) Endpoint Species Value Source EC50 72h Algae or other aquatic plants 51.404mg/l 2 EC50 48h Crustacea 93.313mg/l 2 tartaric acid EC50 96h Algae or other aquatic plants 23616mg/L 2 NOEC(ECx) 72h Algae or other aquatic plants 3.125mg/l 2 LC50 96h Fish >100mg/l 2 Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Legend: Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan)

DO NOT discharge into sewer or waterways.

- Bioconcentration Data 8 Vendor Data

Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|-----------------------------|-------------------------|------------------|
| 2-hydroxyethyl methacrylate | LOW | LOW |

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|--------------------------|-------------------------|------------------|
| acrylic acid homopolymer | LOW | LOW |
| glycerol dimethacrylate | LOW | LOW |
| tartaric acid | LOW | LOW |

Bioaccumulative potential

| Biododinialito potonial | |
|-------------------------|--|
| Bioaccumulation | |
| LOW (BCF = 1.54) | |
| LOW (LogKOW = 0.4415) | |
| LOW (LogKOW = 1.1616) | |
| LOW (LogKOW = -1.0017) | |
| | |

Mobility in soil

| Ingredient | Mobility |
|-----------------------------|--------------------|
| 2-hydroxyethyl methacrylate | HIGH (KOC = 1.043) |
| acrylic acid homopolymer | HIGH (KOC = 1.201) |
| glycerol dimethacrylate | LOW (KOC = 10) |
| tartaric acid | HIGH (KOC = 1) |

SECTION 13 Disposal considerations

| Product / Packaging disposal | DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Consult State Land Waste Management Authority for disposal. Bury residue in an authorised landfill. |
|------------------------------|---|
|------------------------------|---|

SECTION 14 Transport information

| Labels Required | |
|------------------|----------------|
| Marine Pollutant | NO |
| HAZCHEM | Not Applicable |

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

| Product name | Group |
|---------------------------------------|---------------|
| 2-hydroxyethyl methacrylate | Not Available |
| 2-hydroxyethyl methacrylate phosphate | Not Available |
| acrylic acid homopolymer | Not Available |
| glycerol dimethacrylate | Not Available |
| tartaric acid | Not Available |

14.7.3. Transport in bulk in accordance with the IGC Code

| Product name | Ship Type |
|---------------------------------------|---------------|
| 2-hydroxyethyl methacrylate | Not Available |
| 2-hydroxyethyl methacrylate phosphate | Not Available |
| acrylic acid homopolymer | Not Available |
| glycerol dimethacrylate | Not Available |
| tartaric acid | Not Available |

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

²⁻hydroxyethyl methacrylate is found on the following regulatory lists

Page 11 of 12

Riva Luting Plus (liquid)

| Australia Hazardous Chemical Ir | nformation System (HCIS) - Hazardous Chemicals |
|------------------------------------|--|
| Australia Standard for the Unifor | m Scheduling of Medicines and Poisons (SUSMP) - Schedule 5 |
| Australian Inventory of Industrial | Chemicals (AIIC) |
| | |
| | phosphate is found on the following regulatory lists |
| Australian Inventory of Industrial | Chemicals (AIIC) |
| acrylic acid homopolymer is for | ound on the following regulatory lists |
| Australian Inventory of Industrial | Chemicals (AIIC) |
| International Agency for Research | ch on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic |
| | |
| glycerol dimethacrylate is four | nd on the following regulatory lists |
| Not Applicable | |
| tartaric acid is found on the fo | sllowing regulatory lists |
| Australian Inventory of Industrial | Chemicals (AIIC) |
| | |
| National Inventory Status | |
| National Inventory | Status |
| Australia - AIIC / Australia | No (alveoral dimetheory loto) |
| Non-Industrial Use | No (glycerol dimethacrylate) |
| Canada - DSL | No (glycerol dimethacrylate) |
| Canada - NDSL | No (2-hydroxyethyl methacrylate; 2-hydroxyethyl methacrylate phosphate; acrylic acid homopolymer; tartaric acid) |
| | |

| Canada - NDSL | No (2-hydroxyethyl methacrylate; 2-hydroxyethyl methacrylate phosphate; acrylic acid homopolymer; tartaric acid) | |
|-------------------------------|---|--|
| China - IECSC | Yes | |
| Europe - EINEC / ELINCS / NLP | No (acrylic acid homopolymer) | |
| Japan - ENCS | Yes | |
| Korea - KECI | Yes | |
| New Zealand - NZIoC | Yes | |
| Philippines - PICCS | No (glycerol dimethacrylate) | |
| USA - TSCA | Yes | |
| Taiwan - TCSI | Yes | |
| Mexico - INSQ | No (2-hydroxyethyl methacrylate phosphate; glycerol dimethacrylate) | |
| Vietnam - NCI | Yes | |
| Russia - FBEPH | No (2-hydroxyethyl methacrylate phosphate; glycerol dimethacrylate) | |
| Legend: | Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. | |

SECTION 16 Other information

| Revision Date | 10/03/2023 |
|---------------|------------|
| Initial Date | 10/11/2015 |

SDS Version Summary

| Version | Date of Update | Sections Updated |
|---------|----------------|---|
| 10.1 | 23/12/2022 | Classification review due to GHS Revision change. |
| 11.1 | 10/03/2023 | Classification change due to full database hazard calculation/update. |

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by SDI Limited using available literature references

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- PC TWA: Permissible Concentration-Time Weighted Average
- PC STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit.
- IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level Þ
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index Þ DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration

- AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- IECSC: Inventory of Existing Chemical Substance in China
- EINECS: European INventory of Existing Commercial chemical Substances
 ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

The information contained in the Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.

Other information:

Prepared by: SDI Limited 3-15 Brunsdon Street, Bayswater Victoria, 3153, Australia Phone Number: +61 3 8727 7111 Department issuing SDS: Research and Development Contact: Technical Director