

SDI Limited Version No: 11.1

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Issue Date: 10/03/2023 Print Date: 22/11/2023 L.GHS.NZL.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier		
Product name	Riva Luting Plus (liquid)	
Chemical Name	Not Applicable	
Synonyms	Not Available	
Chemical formula	Not Applicable	
Other means of identification	Not Available	

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Professional dental use: Liquid for dental restorative cement.

Details of the manufacturer or supplier of the safety data sheet

Registered company name	SDI Limited	SDI (North America) Inc.	SDI Germany GmbH
Address	3-15 Brunsdon Street Bayswater VIC 3153 Australia	1279 Hamilton Parkway Itasca IL 60143 United States	Hansestrasse 85 Cologne D-51149 Germany
Telephone	+61 3 8727 7111	+1 630 361 9200	+49 0 2203 9255 0
Fax	+61 3 8727 7222	Not Available	+49 0 2203 9255 200
Website	www.sdi.com.au	www.sdi.com.au	www.sdi.com.au
Email	info@sdi.com.au	USA.Canada@sdi.com.au	germany@sdi.com.au
Registered company name SDI HOLDINGS PTY LTD DO			
Address	Rua Dr. Reinaldo Schmithausen 3141 – Cordeiros Itajaí – SC – CEP 88310-004 Brazil		
Telephone	+55 11 3092 7100		
Fax	Not Available		
Website	http://www.sdi.com.au/		
Email	Brasil@sdi.com.au		

Emergency telephone number

Association / Organisation	SDI Limited	CHEMWATCH EMERGENCY RESPONSE (24/7)
Emergency telephone numbers	131126 Poisons Information Centre	+64 800 700 112
Other emergency telephone numbers	+61 3 8727 7111	+61 3 9573 3188

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

Classification ^[1]	Skin Corrosion/Irritation Category 2, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 2, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Hazardous to the Aquatic Environment Long-Term Hazard Category 4	
Legend:	1. Classification by vendor; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	
Determined by using GHS/HSNO criteria	6.3A, 6.4A, 6.5B (contact), 9.1D, 6.1E (respiratory tract irritant)	

Label elements

Hazard pictogram(s

pictogram(s)		
Signal word	Warning	

Hazard statement(s)

H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H335	May cause respiratory irritation.	
H413	May cause long lasting harmful effects to aquatic life.	

Precautionary statement(s) Prevention

P271	Use only outdoors or in a well-ventilated area.	
P280	Wear protective gloves, protective clothing, eye protection and face protection.	
P261	Avoid breathing mist/vapours/spray.	
P273	Avoid release to the environment.	
P264	Wash all exposed external body areas thoroughly after handling.	
P272	Contaminated work clothing should not be allowed out of the workplace.	

Precautionary statement(s) Response

P302+P352	IF ON SKIN: Wash with plenty of water.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.	
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.	
P337+P313	If eye irritation persists: Get medical advice/attention.	
P362+P364	Take off contaminated clothing and wash it before reuse.	
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	

Precautionary statement(s) Storage

P405	Store locked up.	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	

Precautionary statement(s) Disposal

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

P501

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
868-77-9	10-25	2-hydroxyethyl methacrylate
52628-03-2	15-20	2-hydroxyethyl methacrylate phosphate
9003-01-4	5-15	acrylic acid homopolymer
1830-78-0	5-10	glycerol dimethacrylate
87-69-4	1-5	tartaric acid
Legend:	1. Classification by vendor; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available	

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	 If this product comes in contact with eyes: Wash out immediately with water. If irritation continues, seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. 	
Skin Contact	If skin or hair contact occurs: ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.	
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay. 	
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. Seek medical attention. 	

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

Foam.

Dry chemical powder.

- BCF (where regulations permit).
 Carbon dioxide.
- Water spray or fog Large fires only.

Special hazards arising from the substrate or mixture

	New York		
Fire Incompatibility	None known.		
Advice for firefighters			
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water courses. Use water delivered as a fine spray to control fire and cool adjacent area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use. 		
Fire/Explosion Hazard	 Combustible. Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit toxic fumes of carbon monoxide (CO). May emit acrid smoke. Mists containing combustible materials may be explosive. Combustion products include: carbon dioxide (CO2) other pyrolysis products typical of burning organic material. May emit clouds of acrid smoke May emit poisonous fumes. 		

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

May emit corrosive fumes.

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid contact with skin and eyes. Wear impervious gloves and safety goggles. Trowel up/scrape up. Place spilled material in clean, dry, sealed container. Flush spill area with water.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Neutralise/decontaminate residue (see Section 13 for specific agent). Collect solid residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains. After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using. If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling	
Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. DO NOT allow material to contact humans, exposed food or food utensils. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke.

	 Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
Other information	Store in a dry and well ventilated-area, away from heat and sunlight. Store between 5 and 25 deg. C.

Conditions for safe storage, including any incompatibilities

Suitable container	 DO NOT repack. Use containers supplied by manufacturer only. Check that containers are clearly labelled and free from leaks
Storage incompatibility	Avoid strong bases.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2		TEEL-3	
2-hydroxyethyl methacrylate	1.9 mg/m3	21 mg/m3		1,000 mg/m3	
tartaric acid	1.6 mg/m3	17 mg/m3		100 mg/m3	
Ingredient	Original IDLH		Revised IDLH		
2-hydroxyethyl methacrylate	Not Available		Not Available	Not Available	
2-hydroxyethyl methacrylate phosphate	Not Available		Not Available	Not Available	
acrylic acid homopolymer	Not Available	Not Available		Not Available	
glycerol dimethacrylate	Not Available	Not Available		Not Available	
tartaric acid	Not Available	Not Available			

Occupational Exposure Banding			
Ingredient	Occupational Exposure Band Rating Occupational Exposure Band Limit		
2-hydroxyethyl methacrylate	E	≤ 0.1 ppm	
2-hydroxyethyl methacrylate phosphate	E	≤ 0.1 ppm	
acrylic acid homopolymer	E	≤ 0.01 mg/m³	
glycerol dimethacrylate	E ≤ 0.1 ppm		
tartaric acid	E ≤ 0.01 mg/m ³		
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.		

MATERIAL DATA

NOTE D: Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed on Annex I

When they are placed on the market in a non-stabilised form, the label must state the name of the substance followed by the words "non-stabilised"

European Union (EU) List of harmonised classification and labelling hazardous substances, Table 3.1, Annex VI, Regulation (EC) No 1272/2008 (CLP) - up to the latest ATP

Exposure controls

Appropriate engineering controls	be highly effective in protecting workers and will typically be independent of worker interactions to provide this his. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designer ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is e protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensur An approved self contained breathing apparatus (SCBA) may be required in some situations. Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the	and ventilation that strategically d properly. The design of a essential to obtain adequate e adequate protection. possess varying "escape"
	Type of Contaminant:	Air Speed:
	solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)

	aerosols, fumes from pouring operations, intermittent conta drift, plating acid fumes, pickling (released at low velocity ir	0.5-1 m/s (100-200 f/min.)		
	direct spray, spray painting in shallow booths, drum filling, generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)		
	grinding, abrasive blasting, tumbling, high speed wheel ger very high rapid air motion).	2.5-10 m/s (500-2000 f/min.)		
	Within each range the appropriate value depends on:			
	Lower end of the range			
	1: Room air currents minimal or favourable to capture			
	2: Contaminants of low toxicity or of nuisance value only.			
	3: Intermittent, low production.	3: High production, heavy use		
	4: Large hood or large air mass in motion	4: Small hood-local control only		
	Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.			
Individual protection measures, such as personal protective equipment				
Eye and face protection	the wearing of lenses or restrictions on use, should be cr and adsorption for the class of chemicals in use and an their removal and suitable equipment should be readily a remove contact lens as soon as practicable. Lens should	equivalent] enses may absorb and concentrate irritants. A written policy eated for each workplace or task. This should include a revi account of injury experience. Medical and first-aid personnel vailable. In the event of chemical exposure, begin eye irriga be removed at the first signs of eye redness or irritation - le nds thoroughly. [CDC NIOSH Current Intelligence Bulletin 55	ew of lens absorption should be trained in tion immediately and ns should be removed in	
Skin protection	See Hand protection below			
Hands/feet protection	 Rubber Gloves Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber 			
Body protection	See Other protection below			
Other protection	No special equipment needed when handling small quantities OTHERWISE: • Overalls. • Barrier cream. • Eyewash unit.	5.		

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	A-AUS / Class1 P3	-
up to 50	1000	-	A-AUS / Class 1 P3
up to 50	5000	Airline *	-
up to 100	5000	-	A-2 P3
up to 100	10000	-	A-3 P3
100+			Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 Physical and chemical properties

Information on basic physical and chamical properties

information on basic physical and chemical properties			
Appearance	Slightly yellow liquid with slight characteristic odour, mixes with water.		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	<2	Decomposition temperature (°C)	Not Available

Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Riva Luting Plus (liquid)	Not Available	Not Available	
	тохісіту	IRRITATION	
Chronic	Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems. Practical experience shows that skin contact with the material is capable either of inducing a sensitisation reaction in a substantial number of individuals, and/or of producing a positive response in experimental animals. Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological, irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even to tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance who are likely to become hyper-responsive. Substances than can cuase occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing air-way hyper-responsiveness. The latter substances are not classified as asthmagens or respiratory sensitisers Wherever it is reasonably practicable, exposure to substances that can cuase occupational asthma should be prevented. Where this is not possible the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance. Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical s		
Eye	Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.		
Skin Contact	Evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis. The material may accentuate any pre-existing dermatitis condition Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.		
Ingestion	Accidental ingestion of the material may be damaging to the health of the	e individual.	
Inhaled	individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system. Inhalation hazard is increased at higher temperatures. Acute effects from inhalation of high concentrations of vapour are pulmonary irritation, including coughing, with nausea; central nervous system depression - characterised by headache and dizziness, increased reaction time, fatigue and loss of co-ordination		
	Evidence shows, or practical experience predicts, that the material produ	uces irritation of the respiratory system, in a substantial number of	

2-hydroxyethyl methacrylate	Dermal (rabbit) LD50: >3000 mg/kg ^[2]	Eye (rabbit): SEVERE *post-exposure	
	Oral (Rat) LD50: >=2000 mg/kg ^[1]	Eye: adverse effect observed (irritating) ^[1]	
		Skin (rabbit): non-irritating* * Rohm & Haas	
		Skin: no adverse effect observed (not irritating) ^[1]	
	ΤΟΧΙΟΙΤΥ	IRRITATION	
2-hydroxyethyl methacrylate	Oral (Rat) LD50: >2000 mg/kg ^[1]	Eye: adverse effect observed (irritating) ^[1]	
phosphate		Skin: adverse effect observed (corrosive) ^[1]	
		Skin: no adverse effect observed (not irritating) ^[1]	
	ΤΟΧΙΟΙΤΥ	IRRITATION	
	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Eye: adverse effect observed (irreversible damage) ^[1]	
acrylic acid homopolymer	Inhalation(Rat) LC50: >5.1 mg/l4h ^[1]	Skin: no adverse effect observed (not irritating) ^[1]	
	Oral (Rat) LD50: 146-468 mg/kg ^[1]		
glycerol dimethacrylate	ΤΟΧΙΟΙΤΥ	IRRITATION	
	Not Available	Not Available	
	ΤΟΧΙΟΙΤΥ	IRRITATION	
tartaric acid	dermal (rat) LD50: >2000 mg/kg ^[1]	Not Available	
	Oral (Rat) LD50: >=2000<=5000 mg/kg ^[1]		
2-HYDROXYETHYL METHACRYLATE	Dermal (rabbit): >5000 mg/kg* Effects persist beyond 21 days		
2-HYDROXYETHYL METHACRYLATE	No significant acute toxicological data identified in literature search.		
PHOSPHATE			
	Polycarboxylates are of low toxicity by all exposure routes. Homopolymers(P-AA) are of low acute toxicity to the rat (Li irritating to the eye. Further P-AA has no sensitising potent The adverse effect after repeated inhalation dosing (91-d/r substance related owing to the physical property of the res There was neither evidence for a genotoxic potential of PA or reprotoxicity in the rat. Based upon the available data, it to humans The Cosmetic Ingredient Review (CIR) Expert Panel noted pass through the stratum corneum of the skin, so significar expected to result in systemic or reproductive and develop The Panel noted that cosmetic products containing these in membranes. Thus, crosslinked alkyl acrylates could be abs lips,and other mucous membranes, and through ingestion intact mucous membranes is likely to be not significant,prin nature of the polymers precludes degradation to smaller ad Absorption of the polymers and their residual monomers in on the relatively small fractions of the applied products that The Carbomers (Carbopols) are synthetic, high molecular of	examined. D50 > 5 g/kg bw/d) and are not irritating to the rabbit s skin and, at the most, slightly ial. at) was a mild, reversible pulmonary irritation. This effect is considered as not pirable dust, which caused local and not systemic lung effects. A using a variety of genetic endpoints in-vitro and in-vivo, nor for developmental tox is considered that exposure to polycarboxylates does not imply any particular haza that these crosslinked alkyl acrylates are macromolecules that are not expected to t dermal absorption is not expected. Therefore, topically applied cosmetics are not mental toxicity or to have genotoxic or carcinogenic effects upon use. ngredients are reportedly used around the eyes, on the lips, and on other mucous sorbed systemically through the relatively moist, n stratum cornea of the conjunctiva when applied to the lips. However, the Panel noted that any absorption through her narily because of the relatively large molecular sizes. Furthermore, the chemically is	

In al attentative method study, acrylates/nin/ neodecanoate crosspolymer was prediced to be a non-initiation and in arrylates reported no to slight irritation with undiluted and weak sensitization with 2% aq., acrylates/C10-30 alkyl acrylate crosspolymer, no irritation or sensitization with sodium acrylates crosspolymer-2 (concentration not specified). Mostly, human testing with undiluted acrylates/C10-30 alkyl acrylate crosspolymer, and acrylates/ethylhexyl acrylate crosspolymer, no to 2.5% aq., acrylates/vinyl isodecanoate crosspolymer, 1% aq. dilutions of formulations containing 2% acrylates/vinyl neodecanoate crosspolymer, 1% aq. dilutions of formulations containing 2% acrylates/vinyl neodecanoate crosspolymer, and formulations containing up to 2.6% larryl methacrylate/glycol dimethacrylate crosspolymers do not indicate any dermal irritation or sensitization. The only exception was a weak irritant response noted during an intensified Shelanski human repeated insult patch test (HRIPT) with undiluted acrylates/C10-30 alkyl acrylate crosspolymer.

Alternative test methods for ocular irritation indicated that acrylates/vinyl isodecanoate crosspolymer and a formulation containing 1% lauryl methacrylate/glycol dimethacrylate crosspolymer are not likely ocular irritants. In studies using rabbits, undiluted acrylates/C10-30 alkyl acrylate crosspolymer produced minimal to moderate irritation, and it was considered a borderline irritant in unrinsed rabbit eyes. Acrylates crosspolymer, at 50% in olive oil,and sodium acrylates crosspolymer-2 did not appear to be ocular irritants in rabbit eyes. Two different risk assessments evaluating the carcinogenic endpoint for benzene that may be present in acrylates/C10-30 alkyl acrylates crosspolymer resulted in different lifetime risk. One found that the risk was within the range associated with a 10exp 6 cancer risk, while the other reported a 20-fold greater risk.

	Final Safety Assessment: Crosslinked Alkyl Acrylates as Used in Cosmetics. Nov 2011 Cosmetic Ingredient Review (CIR) Expert Panel http://ntp.niehs.nih.gov/ntp/roc/nominations/2013/publiccomm/attachmentcir_508.pdf The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.
GLYCEROL DIMETHACRYLATE	UV (ultraviolet)/ EB (electron beam) acrylates are generally of low toxicity UV/EB acrylates are divided into two groups; "stenomeric" and "eurymeric" acrylates. The first group consists of well-defined acrylates which can be described by a simple idealised chemical;they are low molecular weight species with a very narrow weight distribution profile. The eurymeric acrylates cannot be described by an idealised structure and may differ fundamentally between various suppliers; they are of relatively high molecular weigh and possess a wide weight distribution. Stenomeric acrylates are usually more hazardous than the eurymeric substances. Stenomeric acrylates are also well defined which allows comparison and exchange of toxicity data - this allows more accurate classification. The stenomerics cannot be classified as a group; they exhibit substantial variation. The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the
TARTARIC ACID	spongy layer (spongiosis) and intracellular oedema of the epidemis. Convulsions, haamorrhage recorded. for simple alpha-hydroxy carboxylic acids and their salts: The US Food and Drug Administration (FDA) received a total of 114 adverse dermatologic experience reports for alpha-hydroxy acids (AHA)- containing skin care products between 1992 and February 2004, with the maximum number in 1994. The reported adverse experiences included burning (45), dermatitis or rash (35), swelling (29), pigmentary changes (15), bilsters or wells (14), skin peoling (13), itching (12), iritation or tenderness (6), chemical burns (6), and increased suburn (7). The frequency of such reports for skin excillating products that cause the greatest degree of exfoliation, such as 'skin peelers." Various studies confirmed previous industry studies indicating that applying AHAs to the skin results in increased UV sensitivity to UV-induced cellular damage doubled, on average, with considerable differences among individuals. Topical glycolic acid enhances photodamage by ultraviolet light. However, the studies also indicated that this increase in sensitivity is reversible and does not last long after discontinuing use of the AHA cream. One week after the treatments were halted, researchers found no significant differences in UV sensitivity among the various skin sites. Most AHAs are physiologic, natural, and non-toxic substances. All members of the group promote normal kerainization and desquamation. These studies din oti dentiff variadly sub MHAs bring about the increased UV sensitivity, athrough the effects did not appear to involve dramatic increases in UV-induced damage to DNA in the skin. Previous FDA studies have indicated that a cosmetic-type cream base caused an AHA to panetrate more deeply into the skin when compared to an AHA solution without the usual cosmetic ingredients. However, further studies will be needed to learn how much, if at all, those cosmetic-type ingredients influence the AHA-related effects on UV sen
2-HYDROXYETHYL METHACRYLATE & 2-HYDROXYETHYL METHACRYLATE PHOSPHATE	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.
2-HYDROXYETHYL METHACRYLATE & 2-HYDROXYETHYL METHACRYLATE PHOSPHATE & ACRYLIC ACID HOMOPOLYMER & GLYCEROL DIMETHACRYLATE & TARTARIC ACID	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.
2-HYDROXYETHYL METHACRYLATE PHOSPHATE & GLYCEROL DIMETHACRYLATE	Where no "official" classification for acrylates and methacrylates exists, there has been cautious attempts to create classifications in the absence of contrary evidence. For example Monalkyl or monoarylesters of acrylic acids should be classified as R36/37/38 and R51/53 Monoalkyl or monoaryl esters of methacrylic acid should be classified as R36/37/38 Based on the available oncogenicity data and without a better understanding of the carcinogenic mechanism the Health and Environmental

DIMETHACRYLATE Based on the available oncogenicity data and without a better understanding of the carcinogenic mechanism the Health and Environmental

Review Division (HERD), Office of Toxic Substances (OTS), of the US EPA previously concluded that all chemicals that contain the acrylate or methacrylate moiety (CH2=CHCOO or CH2=C(CH3)COO) should be considered to be a carcinogenic hazard unless shown otherwise by adequate testing. This position has now been revised and acrylates and methacrylates are no longer <i>de facto</i> carcinogens.			rcinogenic hazard unless shown otherwise by
Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	*	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×
			ot available or does not fill the criteria for classification le to make classification

SECTION 12 Ecological information

	Endpoint	Test Duration (hr)		Species	Value	Source
Riva Luting Plus (liquid)	Not Available	Not Available		Not Available	Not Available	Not Availabl
	Endpoint	Test Duration (hr)		Species	Value	Sourc
	EC50	72h		Algae or other aquatic plants	345mg/l	2
-hydroxyethyl methacrylate	EC50	48h		Crustacea	380mg/l	2
	NOEC(ECx)	504h		Crustacea	24.1mg/l	2
	LC50	96h		Fish	>100mg/l	2
	Endpoint	Test Duration (hr)		Species	Value	Sourc
	LC50	96h		Fish	>112mg/l	2
hydroxyethyl methacrylate phosphate	EC50	72h		Algae or other aquatic plants	>120mg/l	2
pilospilate	EC50	48h		Crustacea	68mg/l	2
	NOEC(ECx)	72h		Algae or other aquatic plants	>=30mg/l	2
	Endpoint	Test Duration (hr)		Species	Value	Sourc
	EC50	72h		Algae or other aquatic plants	0.13-0.205mg/l	2
acrylic acid homopolymer	EC50	48h		Crustacea	47mg/l	2
	EC10(ECx)	72h		Algae or other aquatic plants 0.03-0.031		2
	LC50	96h	Fish 27mg/l		27mg/l	2
	Endpoint	Test Duration (hr)		Species	Value	Source
glycerol dimethacrylate	Not Available	Not Available		Not Available	Not Available	Not Availab
	Endpoint	Test Duration (hr)		Species	Value	Sourc
	EC50	72h		Algae or other aquatic plants	51.404mg/l	2
tartaric acid	EC50	48h		Crustacea	93.313mg/l	2
	EC50	96h		Algae or other aquatic plants	23616mg/L	2
	NOEC(ECx)	72h		Algae or other aquatic plants	3.125mg/l	2
	LC50	96h		Fish	>100mg/l	2
Legend:	Extracted from	1. IUCLID Toxicity Data 2. Europe E0	CHA Registered	d Substances - Ecotoxicological Informa	tion - Aquatic Toxicity 4.	US EPA.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
2-hydroxyethyl methacrylate	LOW	LOW
acrylic acid homopolymer	LOW	LOW
glycerol dimethacrylate	LOW	LOW
tartaric acid	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
2-hydroxyethyl methacrylate	LOW (BCF = 1.54)

Bioaccumulation
LOW (LogKOW = 0.4415)
LOW (LogKOW = 1.1616)
LOW (LogKOW = -1.0017)

Mobility in soil	
Ingredient	Mobility
2-hydroxyethyl methacrylate	HIGH (KOC = 1.043)
acrylic acid homopolymer	HIGH (KOC = 1.201)
glycerol dimethacrylate	LOW (KOC = 10)
tartaric acid	HIGH (KOC = 1)

SECTION 13 Disposal considerations

Waste treatment methods	
Product / Packaging disposal	 DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Consult State Land Waste Management Authority for disposal. Bury residue in an authorised landfill.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous. Only dispose to the environment if a tolerable exposure limit has been set for the substance.

Only deposit the hazardous substance into or onto a landfill or sewage facility or incinerator, where the hazardous substance can be handled and treated appropriately.

SECTION 14 Transport information

Labels Required	
Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
2-hydroxyethyl methacrylate	Not Available
2-hydroxyethyl methacrylate phosphate	Not Available
acrylic acid homopolymer	Not Available
glycerol dimethacrylate	Not Available
tartaric acid	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
2-hydroxyethyl methacrylate	Not Available
2-hydroxyethyl methacrylate phosphate	Not Available
acrylic acid homopolymer	Not Available
glycerol dimethacrylate	Not Available
tartaric acid	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard			
HSR002521	Animal Nutritional and Animal Care Products Group Standard 2020			
HSR002530	Cleaning Products Subsidiary Hazard Group Standard 2020			
HSR002535	Gases under Pressure Mixtures Subsidiary Hazard Group Standard 2020			
HSR002503	Additives Process Chemicals and Raw Materials Subsidiary Hazard Group Standard 2020			
HSR002606	Lubricants Lubricant Additives Coolants and Anti freeze Agents Subsidiary Hazard Group Standard 2020			
HSR002612	Metal Industry Products Subsidiary Hazard Group Standard 2020			
HSR002624	N.O.S. Subsidiary Hazard Group Standard 2020			
HSR002638	Photographic Chemicals Subsidiary Hazard Group Standard 2020			
HSR002644	Polymers Subsidiary Hazard Group Standard 2020			
HSR002647	Reagent Kits Group Standard 2020			
HSR002648	Refining Catalysts Group Standard 2020			
HSR002653	Solvents Subsidiary Hazard Group Standard 2020			
HSR002670	Surface Coatings and Colourants Subsidiary Hazard Group Standard 2020			
HSR002684	Water Treatment Chemicals Subsidiary Hazard Group Standard 2020			
HSR100425	Pharmaceutical Active Ingredients Group Standard 2020			
HSR002600	Leather and Textile Products Subsidiary Hazard Group Standard 2020			
HSR002544	Construction Products Subsidiary Hazard Group Standard 2020			
HSR002549	Corrosion Inhibitors Subsidiary Hazard Group Standard 2020			
HSR002552	Cosmetic Products Group Standard 2020			
HSR002558	Dental Products Subsidiary Hazard Group Standard 2020			
HSR002565	Embalming Products Subsidiary Hazard Group Standard 2020			
HSR002571	Fertilisers Subsidiary Hazard Group Standard 2020			
HSR002573	Fire Fighting Chemicals Group Standard 2021			
HSR002578	Food Additives and Fragrance Materials Subsidiary Hazard Group Standard 2020			
HSR002585	Fuel Additives Subsidiary Hazard Group Standard 2020			
HSR002596	Laboratory Chemicals and Reagent Kits Group Standard 2020			
HSR100757	Veterinary Medicines Limited Pack Size Finished Dose Group Standard 2020			
HSR100758	Veterinary Medicines Non dispersive Closed System Application Group Standard 2020			
HSR100759	Veterinary Medicines Non dispersive Open System Application Group Standard 2020			

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

2-hydroxyethyl methacrylate is found on the following regulatory lists

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data New Zealand Inventory of Chemicals (NZIoC)

2-hydroxyethyl methacrylate phosphate is found on the following regulatory lists

New Zealand Inventory of Chemicals (NZIoC)

acrylic acid homopolymer is found on the following regulatory lists

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic New Zealand Inventory of Chemicals (NZIoC)

New Zealand Land Transport Rule: Dangerous Goods 2005 - Schedule 1 Quantity limits for dangerous goods

glycerol dimethacrylate is found on the following regulatory lists

New Zealand Inventory of Chemicals (NZIoC)

tartaric acid is found on the following regulatory lists

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

Additional Regulatory Information

Not Applicable

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantities
Not Applicable	Not Applicable

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance

Quantities

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
6.5A or 6.5B	120	1	3	

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory Status		
Australia - AIIC / Australia Non-Industrial Use	No (glycerol dimethacrylate)	
Canada - DSL	No (glycerol dimethacrylate)	
Canada - NDSL	No (2-hydroxyethyl methacrylate; 2-hydroxyethyl methacrylate phosphate; acrylic acid homopolymer; tartaric acid)	
China - IECSC	Yes	
Europe - EINEC / ELINCS / NLP	No (acrylic acid homopolymer)	
Japan - ENCS	/es	
Korea - KECI	Yes	
New Zealand - NZIoC	Yes	
Philippines - PICCS	No (glycerol dimethacrylate)	
USA - TSCA	Yes	
Taiwan - TCSI	Yes	
Mexico - INSQ	No (2-hydroxyethyl methacrylate phosphate; glycerol dimethacrylate)	
Vietnam - NCI	Yes	
Russia - FBEPH	No (2-hydroxyethyl methacrylate phosphate; glycerol dimethacrylate)	
Legend: Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.		

SECTION 16 Other information

Revision Date	10/03/2023
Initial Date	10/11/2015

SDS Version Summary

Version	Date of Update	Sections Updated
10.1	23/12/2022	Classification review due to GHS Revision change.
11.1	10/03/2023	Classification change due to full database hazard calculation/update.

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by SDI Limited using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- PC TWA: Permissible Concentration-Time Weighted Average
- PC STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- ► TEEL: Temporary Emergency Exposure Limit.
- IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
 LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- I OD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index
- DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
- AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List

- NDSL: Non-Domestic Substances List
- IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
 ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
 PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- + FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

The information contained in the Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.

Other information:

Prepared by: SDI Limited 3-15 Brunsdon Street, Bayswater Victoria, 3153, Australia Phone Number: +61 3 8727 7111 Department issuing SDS: Research and Development Contact: Technical Director

